



Get the most value for your money with Epson business projectors! These projectors are designed to be your choice regardless if they are used in a corporate setting or in the educational field. Now you are able to showcase your content crisp and clear on large screens.



EB-E10



EB-972



12,000 Hours Lamp Life in Eco Mode<sup>1</sup>



Split Screen



Auto Vertical Keystone



Horizontal Keystone Slider<sup>2</sup>



iProjection



Cost Effective



**IT'S IN THE DETAILS.**

3LCD technology that delivers quality projected images and reliable performance.

<sup>1</sup> Up to 17,000 hours lamp life in Eco Mode for EB-972. <sup>2</sup> Except EB-E10.

## SPECIFICATIONS EB-E10/972

**EPSON**  
EXCEED YOUR VISION

MODEL NUMBER	EB-E10	EB-972
<b>Projection Technology</b>	RGB liquid crystal shutter projection system (3LCD)	
<b>Specifications of Main Parts</b>		
LCD	Size	0.55" (C2fine)
	Native Resolution	XGA (1024 x 768)
Lightsource	Type	210W UHE
	Life (Normal / Eco)	6,000 / 12,000 hours
Aspect Ratio	4:3	
Projection Lens	Type	No Optical Zoom (Manual) / Focus (Manual)
	F-Number	1.44
	Focal Length	16.70 mm
	Zoom Ratio	1.00 – 1.35 (Digital Zoom)
	Throw Ratio	1.44 – 1.85 (Wide to Tele)
		Optical Zoom (Manual) / Focus (Manual)
	1.51 – 1.99	
	18.20 – 29.20 mm	
	1 – 1.6	
	1.58 – 2.56 (Wide to Tele)	
<b>Screen Size (Projected Distance)</b>		
Standard	Tele: 22" to 259" [0.67 to 10.34 m] Wide: 30" to 350" [0.87 to 10.34 m]	Tele: 27" to 262" [1.40 to 13.81 m] Wide: 27" to 262" [0.85 to 8.52 m]
<b>Brightness<sup>1</sup></b>		
White Light Output (Normal / Extended)	3,600 lm	4,100 lm
Colour Light Output	3,600 lm	4,100 lm
Contrast Ratio	15,000:1	16,000:1
<b>Geometric Correction</b>		
Vertical / Horizontal Keystone	±30° / ±30°	±30° / ±30° (Auto Vertical Keystone only)
Quick Corner	Yes	
Split Screen	Yes	
Internal Speakers	Monoaural: 2W x 1	Monoaural: 16W x 1
<b>Connectivity</b>		
Analog Input	D-Sub 15Pin	1
	Composite	NA
Digital Input	DVI-D	NA
	HDMI	1
Output Terminal	HDBaseT	NA
	D-Sub 15Pin	NA
Audio Input	HDMI	1
	2RCA (White & Red)	NA
Audio Output	Stereo Mini	NA
	Stereo Mini Jack	NA
Others	USB Type A	1 (for Wireless LAN, Firmware Update, Copy OSD Settings)
	USB Type B	1 (for Firmware Update, Copy OSD Settings)
Mic Input	Stereo Mini	NA
Control I/O	RS-232C	NA
Network	Remote Control Input	NA
	Wired LAN	NA
Wireless	NA	1 (ELPAP11)
<b>Wireless Specification</b>		
Supported Speed For Each Mode		IEEE 802.11b (2.4GHz): 11 Mbps <sup>2</sup> / IEEE 802.11g (2.4GHz): 54 Mbps <sup>2</sup> / IEEE 802.11n (2.4GHz): 72.2 Mbps <sup>2</sup> / IEEE 802.11a (5GHz): 54 Mbps <sup>3</sup> / IEEE 802.11n (5GHz): 150 Mbps <sup>2</sup>
Wireless LAN Security		Infrastructure: OPEN, WPA2/WPA3-PSK Access Point: OPEN, WPA2-PSK (AES)
<b>Operating Temperature</b>	Low Altitude: 5 – 40 °C (<41 – 104 °F) High Altitude: 5 – 35 °C <41 – 95 °F> (20% – 60% Humidity, No Condensation)	
<b>Operating Altitude</b>	0 – 3,048 m (<0 – 10,000 ft>)	
<b>Direct Power On / Off</b>	Yes	
<b>Start-Up Period</b>	Up to 6 seconds, Warm-up Period: 30 seconds	
<b>Cool Down Period</b>	Instant Off	
<b>Air Filter</b>		
Type	High Efficiency Filter	
Maintenance Cycle (Normal / Eco)	6,000 / 12,000 hours <sup>3</sup>	10,000 / 20,000 hours <sup>3</sup>
<b>Power Supply Voltage</b>	100 – 240 V AC ±10%, 50/60 Hz	
<b>Power Consumption (220 - 240V)</b>		
Lamp (Normal / Medium / Eco)	327W / NA / 225W	327W / 290W / 225W
Standby (Network / Energy Saving)	0.3W	2.0W / 0.3W
<b>Dimension Excluding Feet (D X W X H)</b>	234 x 302 x 77 mm	282 x 308 x 90 mm
<b>Weight (Including Standard Lens)</b>	Approx. 2.4 kg	Approx. 3.1 kg
<b>Fan Noise (Normal / Quiet)</b>	37dB / 28dB	

<sup>1</sup> Colour brightness (colour light output) and white brightness (white light output) will vary depending on usage conditions. Colour light output measured in accordance with JMS 15-1; white light output measured in accordance with ISO 21118.

<sup>2</sup> Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, the environment and other factors.

<sup>3</sup> When used in the general office environment (the amount of floating dust: 0.04 - 0.2 mg/m<sup>3</sup>). Based on the Epson's in-house test results.

### EB-E10

#### Supplied Accessories

Power Cable (1.8m)  
Remote control with 2AA Battery  
User's Manual CDROM  
Quick Start Guide  
Soft Carry Case

#### Optional Accessories

Spare Lamp: ELPLP97  
Air Filter: ELPAF32  
Ceiling Mount: ELPMB23

### EB-972

#### Supplied Accessories

Power Cable (1.8m)  
Connection Cable (1.8m)  
Remote control with 2AA Battery  
Cover for Optional Wireless Dongle  
User's Manual CDROM  
Quick Start Guide  
Soft Carry Case

#### Optional Accessories

Spare Lamp: ELPLP97  
Air Filter: ELPAF54  
Wireless LAN: ELPAP11  
Ceiling Mount: ELPMB23



EB-E10



EB-972

©2020 Epson Singapore Pte Ltd. All Rights Reserved. Reproduction in part or in whole, without the written permission from Epson, is strictly prohibited.

EPSON and EXCEED YOUR VISION are registered trademarks of Seiko Epson Corporation.

All other product names and other company names used herein are for identification purposes only and are the trademarks or registered trademarks of their respective owners.

Epson disclaims any and all rights in those marks. Projected images shown herein are simulations. The actual product design and contents may vary. Specifications are subject to change without notice and may vary between countries. Please check with local Epson offices for more information.

Apple, iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc.

Android is a trademark of Google Inc.

Dealer's Stamp

Information correct at time of printing.  
Printed August 2020



To find out more, visit [www.epson.com.my/projectors](http://www.epson.com.my/projectors) or call 1800-81-7349 (Toll-Free).



EpsonMalaysia



EpsonSoutheastAsia



Check for your warranty terms at  
[www.epson.com.my/warrantytc](http://www.epson.com.my/warrantytc)