

## Designer Styling – Big Screen Impact



Small and stylish, the DS306i will deliver life-like presentations and movies up to 300". Great colours, really impressive brightness and easy to use both in the office and at home; with computers, games consoles and DVD players.

- 2300 ANSI Lumens to highlight the finest detail in ambient light conditions
- Designer styling and compact at 2kg; as versatile on the move as it is when installed
- BrilliantColor™ and 2000:1 contrast gives exceptional colour to create crystal clear presentations and video
- Optoma 5 Year Colour Guarantee\*
- 5 Year Imager Guarantee providing consistent pixel performance\*\*\*
- Comprehensive PC, Video, DVD and games consoles connectivity includes: VGA, Component & SCART capabilities
- Native SVGA and zoom lens – for sharp, detailed images and movies
- DLP® Filter-free design for zero maintenance – No routine servicing


### Easy to use:

- Fully featured remote control with mouse control
- 5 preset picture modes to adjust the settings to match a variety of different applications
- 15 second start-up and cool down time to reduce both time and money in energy use
- Quick keystone correction

- Express start-up & cool down
- Built in speaker for multi media use
- Long Lamp Life – 3000 hours standard

BrilliantColor™ maximises colour accuracy for deeper saturated colours

Optoma guarantees colour quality will remain as new for 5 years\*



BrilliantColor™

## Specifications

	DS306i
Native Resolution	SVGA 800 x 600
Compressed Resolution	Up to UXGA (1600 x 1200)
Brightness	2300 ANSI Lumens
Contrast	2000:1
Noise Level	30dB
Lamp Life**	3000/2000 (STD/BRIGHT mode)
Display Technology	Single 0.55" SVGA type X DMD chip DLP® Technology by Texas Instruments
Weight / Dimensions (W x D x H)	2 kg / 259 x 188 x 71.5mm
Remote Control	Full Function Remote Mouse and Direct Source selecting
INPUTS:	15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Stereo Jack USB (remote mouse)
Audio	1 x 1W Speaker
Aspect Ratio	4:3 Native, 16:9 Compatible
Keystone Correction	± 40 Degrees Vertical
On Screen Display	16 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech & Arabic
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i
Uniformity	85%
Displayable Colours	16.7 Million
Projection Lens	F=2.41 ~ 2.55, f=21.79 ~ 23.99mm, 1.1x Manual Focus
Throw Ratio	1.95 ~ 2.15:1 (Projection Distance:Image Width)
Projection Distance	1.2 - 12m
Image Size	0.70 - 7.70m (27.49" - 303.12") Diagonal 4:3
Horizontal Scan Rate	15 - 100kHz
Vertical Scan Rate	43 - 85Hz
Power Supply	100-240V, 50-60Hz with PFC Power Supply
Power Consumption	237W BRIGHT mode < 10W Standby mode 211W STD mode < 10W Standby mode
Operating Conditions	Operating: 5 - 40 °C, 80% Humidity (Max), 3000m Altitude (Max)
Security	One Kensington Lock Port, Password Protection
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, USB Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty, WEEE Card
RoHS	Compliant
Lamp Warranty	6 months or 1000 hours - whichever is soonest
Warranty	Warranty may vary by country. Please see <a href="http://www.optomaeurope.com">www.optomaeurope.com</a> or ask your local supplier for details
Colour Guarantee*	5 Years



### DS306i Remote Control

- 1 Remote Mouse
- 2 Vertical Keystone Correction
- 3 Volume Control
- 4 Brightness Adjustment
- 5 Contrast Adjustment
- 6 AV Mute
- 7 Direct Input Source Selection

### DS306i Connections

- 8 VGA In – Component & SCART via adaptor
- 9 Composite
- 10 S-Video
- 11 Audio In
- 12 USB (Remote Mouse)



### DS306i Projection Distance 1.2 - 12m (16:10 Aspect Ratio)

Projection Distance (m)	Max. Horizontal Image size (m)	Min. Horizontal Image size (m)	Max. Screen Height (m)	Min. Screen Height (m)	Max. Diagonal Image Size (m)	Max. Diagonal Image Size (Inch)	Max. Image Offset (m)
1.20	0.80	0.67	0.50	0.42	0.94	37.14	0.14
2.00	1.33	1.11	0.83	0.69	1.57	61.90	0.23
2.50	1.67	1.39	1.04	0.87	1.97	77.38	0.29
3.00	2.00	1.67	1.25	1.04	2.36	92.85	0.35
4.00	2.67	2.22	1.67	1.39	3.14	123.81	0.47
5.00	3.33	2.78	2.08	1.74	3.93	154.76	0.58
6.00	4.00	3.33	2.50	2.08	4.72	185.71	0.70
7.00	4.67	3.89	2.92	2.43	5.50	216.66	0.82
8.00	5.33	4.44	3.33	2.78	6.29	247.61	0.93
9.00	6.00	5.00	3.75	3.13	7.08	278.56	1.05
10.00	6.67	5.56	4.17	3.47	7.86	309.51	1.17
11.00	7.33	6.11	4.58	3.82	8.65	340.47	1.28
12.00	8.00	6.67	5.00	4.17	9.43	371.42	1.40

For guide purposes only

DS306i is capable of 16:9 & 4:3 aspect ratio projection. When projecting a 16:9 & 4:3 image the image sizes, screen height and offset information will differ to that of above.

Panoview

ProSelecta

View :: Compare :: Select - [www.ProSelecta.com](http://www.ProSelecta.com)