






MULTIMEDIA PROJECTORS

DS339 / DX339 / DW339



EASY PROJECTION, EXCELLENT PERFORMANCE, UNBEATABLE VALUE



-  **Maximum cost/performance ratio and easy maintenance offers an affordable option**
-  **Pre-calibrated image settings create compelling visuals for work or home**
-  **High contrast ratio ensures optimal pictures and video quality**
-  **Comprehensive connectivity provides ultimate flexibility**
-  **Included IR remote mouse with laser pointer for presentations**



The budget-friendly Optoma D-Series projectors deliver first-rate projection power with a comprehensive feature set. Perfect for a broad range of uses, from home to office. This family of projectors, 2,600 lumens bright and 5,000:1 contrast ratio ensure clear and colorful text and brilliant graphics and videos. Choose between SVGA, XGA or WXGA resolutions to best fit your needs. Meanwhile, HDMI allows quick and easy connection to a variety of sources and an IR remote with mouse supports powerful presentations. A top-loading lamp design and long-life lamp minimize time and cost associated with maintenance.

CONNECTIVITY (May require optional accessories)

ProSelecta

View :: Compare :: Select - www.ProSelecta.com

MULTIMEDIA PROJECTORS — DS339/DX339/DW339

OPTICAL/TECHNICAL SPECIFICATIONS

Display Technology	DS & DX – Single 0.55" DC3 DMD DLP DW – Single 0.65" DMD DLP (Technology by Texas Instruments)
Native Resolution	DS – SVGA (800 x 600) DX – XGA (1024 x 768) DW – WXGA (1280 x 800)
Maximum Resolution	UXGA (1600 x 1200) & 1080p (1920 x 1080)
Brightness	2600 ANSI lumens
Contrast Ratio	5,000:1 (full on/full off)
Displayable Colors	1.07 Billion
Lamp Life and Type*	6500/5000/4500 Hours (ECO+/ECO/normal) 190W Philips
Projection Method	Front, rear, ceiling mount, table top
Keystone	±40° Vertical
Uniformity	> 85%
Aspect Ratio	DS & DX – 4:3 Native, 16:9 & 16:10 compatible DW – 16:10 Native, 16:9 and 4:3 compatible
Throw Ratio (Distance/Width)	DS & DX – 1.95 to 2.15 (distance/width) DW – 1.55 to 1.7 (distance/width)
Projection Distance	3.3' to 39.4' (1 to 12 m)
Image Size (Diagonal)	DS & DX – 22.9" to 300" (0.58 to 7.62m) DW – 27.2" to 301" (0.7 to 7.64 m)
Projection Lens	DS & DX – F=2.41~2.55, f=21.8~23.98mm DW – F=2.5 ~ 2.67, f=21.8 ~ 23.98 mm (1.1x manual zoom and focus)
Offset	DS & DX – 115%, DW – 112%
Audio	2-Watt speaker
Noise Level	32dB/34dB
Remote Control	IR remote with mouse control and laser
Operating Temperature	41 to 113° F (5 to 45° C), 85% max humidity
Power Supply	AC Input 100-240V, 50-60 Hz, auto-switching
Power Consumption	Max 263W (Normal), 200W (ECO+) <0.5W (standby-ECO)

COMPATIBILITY SPECIFICATIONS

Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh compatible
Video Input Compatibility	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility**	120Hz frame sequential 3D for resolutions up to 720p, 60Hz field sequential 3D for resolutions up to 480i
Vertical Scan Rate	24 to 85 Hz, 120 Hz
Horizontal Scan Rate	15.3 to 91.1 KHz
User Controls	Complete on-screen menu in 27 languages
I/O Connection Ports	HDMI v1.3, two VGA-in, VGA-out, S-video, composite video, audio-in, audio-out, RS-232, USB-B
Loop Through (Audio, VGA)	Monitor: D-Sub 15 pin VGA output (functional in normal and standby modes)

PHYSICAL SPECIFICATIONS

Security	Kensington® lock port, security bar and keypad lock
Weight	5 lbs (2.27 kg)
Dimensions (W x H x D)	11.3" x 3.5" x 9.3" (287 x 88.9 x 236.2mm)

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

**3D content can be viewed with active LCD shutter glasses or RF glasses when projector is used with compatible 3D player. Please visit www.optoma.com for more information.



Warranty

One-year parts and labor, 90 days on lamp

What Comes in the Box

AC power cord, VGA to VGA cable, remote control, batteries for remote, carrying case, multilingual CD-ROM user's manual, quick start card and warranty card

Optional Accessories

HDMI cable, ceiling mount, VGA to component cable, DLP Link glasses, composite video cable, RS-232 cable and Optoma screens

Part Numbers

Lamp: BL-FU190A

Remote: BR-5041L

UPC

DS339 – 796435 41 772 7

DX339 – 796435 41 776 5

DW339 – 796435 41 778 9

www.OptomaUSA.com

Optoma
Projector Expert

Copyright © 2012 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All other trademarks are the property of their respective owners. All specifications subject to change at any time.