

HL10

Portable LED home entertainment projector









- Bright 1080p LED projector 1500 LED Brightness
- Truly portable Built-in battery
- Easy to setup Auto keystone and four corner adjustment
- Optional wireless presentations

This small 1080p LED projector is ideal for watching live sport, TV shows or movies on a big screen. You can even connect your games console and play games on it with its low input latency.



Specifications

mm

-	
Display/image	
Display technology	DLP
Resolution	1080p Full HD (1920x1080)
Brightness (LED)	1,500 LED brightness
Contrast ratio	200,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3,16:9
Keystone correction -	+/-20°
horizontal	
Keystone correction - vertical	+/-30°
Has vertical auto keystone correction	Yes
Horizontal scan rate	15 ~ 93Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	85%
Screen size	0.47m ~ 2.84m (18.6" ~ 111.8") diagonal
Lamp info	
Light source type	LED
LED life	30,000 hours
Optical	
Throw ratio	1.2:1
Projection distance (m)	0.49m - 2.97m
Zoom type	Fixed
Focal length (mm)	12.64
Native offset	100%
Connectivity	
Connections	Inputs 2 x HDMI, 1 x USB-A wireless
	Outputs 1 x USB-A power 1.5A, 1 x Audio 3.5mm
General	
Noise level (typical)	
	30dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese
PC compatibility OSD / display languages	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
PC compatibility OSD / display languages 24/7 operation	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes
PC compatibility OSD / display languages 24/7 operation Operating conditions	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+,
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+,
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ WHD200, WUSB
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power Power Power supply Power consumption	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power Power supply Power consumption (standby)	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ WHD200, WUSB 100 ~ 240V, 50 ~ 60Hz 0.5W
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power Power supply Power consumption (standby) Battery life	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ WHD200, WUSB
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power Power supply Power consumption (standby) Battery life Weight and dimensions	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ WHD200, WUSB 100 ~ 240V, 50 ~ 60Hz 0.5W Up to 2.5hrs
PC compatibility OSD / display languages 24/7 operation Operating conditions Remote control Speaker count Watts per speaker In the box Operating system compatibility Optional wireless models Power Power supply Power consumption (standby) Battery life	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac 25 languages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese Yes 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m Yes 2 4W Carry bag AC power cord Remote control 2x AAA batteries Basic user manual Windows 7 / 8 / 8.1 / 10, MacOSX 10.9 +, Android 4.0+, iOS 8+ WHD200, WUSB 100 ~ 240V, 50 ~ 60Hz 0.5W



