

S322e

Bright projection



- Bright SVGA projector 3800 ANSI lumens
- Amazing colour technology
- Energy saving features
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day. Designed for meeting rooms and classrooms, the S322e boasts amazing colour, long lamp life and energy-saving features for a low overall cost of ownership.

This projector can easily be connected to a PC or laptop for a clear projected image. It is also portable and lightweight for use on the move at off-site meetings with the optional carry bag (sold separately).

Specifications

| Specifications | |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Display/image | |
| Display technology | DLP |
| Resolution | SVGA (800x600) |
| Brightness | 3,800 lumens |
| Contrast ratio | 22,000:1 |
| Native aspect ratio | 4:3 |
| Aspect ratio - compatible | 16:9 |
| Keystone correction - vertical | 40 |
| Horizontal scan rate | 15.38 ~ 91.15Khz |
| Vertical scan rate | 50 ~ 85(120 for 3D)Hz |
| Uniformity | 75% |
| Screen size | 0.71m - 7.73m (27.78in - 304.4in) |
| Lamp info | |
| Light source | Lamp |
| Lamp watts | 203 |
| Lamp life (hours) | 6000 (Bright), 1200 (Dynamic), 10000 (Eco), 15000 (Eco+) |
| Optical | 1110 (Bilging), 1200 (B). Mailio), 10000 (E00), 10000 (E00T) |
| Throw ratio | 1.94:1 - 2.16:1 |
| Projection distance (m) | 1m - 12m |
| Zoom | 1.1 |
| Zoom type | Manual |
| Focal length (mm) | 21.85 ~ 24 |
| Native offset | 21.65 ~ 24 115% |
| | 115% |
| Connectivity Connections | |
| Connections | Inputs 1 x VGA (YPbPr/RGB), 1 x Composite video |
| | Outputs 1 x USB-A power 1A |
| General | |
| Noise level (typical) | 27dB |
| PC compatibility | FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac |
| 2D compatibility | NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N, 4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz) |
| 3D | 3D ready |
| Security | Security bar, Kensington Lock, Password protected interface |
| OSD / display languages | 25 Ianguages: Arabic, Czech, Danish, Dutch, English, Farsi, Finnish, French, German, Greek, Hungarian, Indonesian, Italian, Japanese, Norwegian, Polish, Portuguese, Romanian, Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese |
| Operating conditions | 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m |
| Remote control | Card style |
| In the box | AC power cord Remote control Battery Basic user manual |
| Power | |
| Power supply | 100 ~ 240V, 50 ~ 60Hz |
| Power consumption (standby) | 0.5W |
| Power consumption (max) | 225W |
| Weight and dimensions | |
| Net weight | 3kg |
| Dimensions (W x D x H) (mm) | 316 x 244 x 108 |



