

GT770



HD-Ready Short Throw Gaming Projector



Features

- Project a 120" image from less than five feet away for a cinematic experience
- Excellent companion for Nintendo Switch, Xbox One S and PS4
- Bright 3,600 lumens image and remarkable 20,000:1 contrast ratio for amazing quality
- Full 3D delivers an immersive gaming experience
- Long lamp life up to 10,000 hours for economical operation
- Bring gaming to any room in the house or gaming night out at a friend's house

Immersive gaming and movie experience from several feet away

Upgrade your game time with a large image with the 3,600 lumens, HD compatible and short throw Optoma GT770 projector. The 0.52:1 short throw lens enables 120-inch projections from less than five feet away for an immersive gaming experience in space-constrained environments.

Vertical keystone support simplifies placement for easy installation while robust input options, including HDMI, VGA and composite enable connectivity to a wide range of new and legacy gaming devices. Up to 10,000 hours of lamp life enable many years of use with minimal maintenance.



ProSelecta

View :: Compare :: Select - www.ProSelecta.com

GT770



TECHNICAL SPECIFICATIONS

| | |
|------------------------------|---|
| Aspect Ratio | 16:10 (native), 16:9, 4:3, LBX and auto compatible |
| Audio | 10W speaker |
| Brightness | 3,600 ANSI lumens |
| Color Wheel | RYGCWB |
| Connections | 1x HDMI, 1x HDMI(MHL), 2x VGA, 1 x VGA out, 1x composite, 1x USB, 1x audio in, 1x audio out, 1x Mic in, 1x RS232, 1x RJ45 |
| Contrast Ratio | 20,000:1 |
| Control Unit | Crestron RoomviewRS-232, RJ45 |
| Display Technology | Texas Instruments 0.65" WXGA DMD |
| Displayable Colors | 1.07 billion |
| Geometry | Vertical keystone |
| Image Size | 35.64" - 302.98" |
| Keystone Correction | ±20° Vertical |
| Light Source Life | Up to 10,000/10,000/6000 (Dynamic/Eco/Bright) |
| Light Source Type | 203W Lamp |
| Maximum Resolution | 1080p (WUXGA) |
| Noise Level | 28dB (Eco) |
| Offset | 115% ±5% |
| Operating Temperature | 41-104°F (5-40°C), 85% max humidity |
| Power Consumption | 243W typical (Bright), 267W max (Bright), 237W typical (Eco), 261W max (Eco) |
| Power Supply | AC input 100-240V, 50-60Hz, auto-switching |

| | |
|----------------------------|---------------------------------------|
| Projection Distance | 1.31' - 11.15' |
| Projection Lens | F=2.8, f=7.51mm |
| Projection Method | Front, rear, ceiling mount, table top |
| Remote Control | Full size remote |
| Resolution | 720p (WXGA) |

COMPATIBILITY SPECIFICATIONS

| | |
|-------------------------------|---|
| 3D Compatibility | Supports all HDMI 1.4a mandatory 3D formats (Frame pack, side-by-side, top-bottom) and up converts frame rate from 60Hz to 120Hz or 24Hz to 144Hz. 3D glasses are needed and are sold separately. |
| Computer Compatibility | VGA, SVGA, HDTV(720P), WXGA, WXGA+, SXGA, SXGA+, UXGA, HDTV(1080p), WUXGA |
| Horizontal Scan Rate | 15.375-91.146 KHz |
| Vertical Scan Rate | 50-85 Hz (120Hz for 3D feature projector) |
| Video Compatibility | PAL, SECAM, 576i/p, NTSC, 480i/p, HDTV 720p/1080i/1080p |

PHYSICAL SPECIFICATIONS

| | |
|-------------------|------------------------|
| Dimensions | 12.44" x 4.27" x 9.56" |
| Security | Kensington® lock port |
| Weight | 6.7 lbs. |

Other

| | |
|---------------------------------|--|
| What's in the Box? | GT770, AC power cord, remote control, batteries, quick start user manual |
| Accessories Part Numbers | Lamp (replacement): BL-FU200D Mounting Plate: BM-4002p Remote (replacement): BR-5053C Universal wall mount: OWM3000ST |
| UPC | 796435825775 |
| Warranty Info | 1 Year limited parts and labor warranty on the projector, 90 days lamp warranty |

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2020 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 10/30/20