

TX540 – Multimedia Projector

Best in Class

Optoma's TX540 is designed to meet the demanding requirements of school districts and businesses. Bright, high contrast images provide easy-to-read text, and the built-in closed captioning decoder displays text from videos that have closed captioning embedded in the signal. Wired networking allows remote management and control of the projector, and a built-in 10-watt speaker system outputs volume required for larger audiences. Optoma backs the TX540 with 3 years of Express Replacement Service and a one year lamp warranty to provide added peace of mind.



Features

- Easy-to-read text – bright at 2600 ANSI lumens and high 2500:1 contrast ratio
- Broadcast messages to projector over the network
- Eco-friendly low power consumption – sub-one watt standby mode
- Remote management and control via RS-232 or RJ45
- Protect your investment – built-in security bar, control panel lock, logo display at start-up and user-selectable password
- Built-in closed captioning



Specifications

Display Technology
Single 0.55" DMD DLP®
Technology by Texas Instruments

Resolution
Native XGA (1024 x 768)

Maximum Resolution
UXGA (1600 x 1200)

Brightness (Typical)
2600 ANSI Lumens

Contrast Ratio
2500:1 (Full On/Full Off)

Lamp Life and Type
5000/4000 Hours (STD/Bright)
180W P-VIP

Throw Ratio
1.6 to 1.92:1 (Distance/Width)

Projection Distance
3.93' to 32.8' (1.2 to 10m)

Image Size (Diagonal)
30" to 307" (0.92 to 9.21m)

Aspect Ratio
4:3 Native, 16:9 and 16:10
Compatible

Remote Control
Fully Featured IR Remote with
Mouse and Laser Pointer

Audio
Two 5-Watt Stereo Speakers

Displayable Colors
1.07 Billion

Offset
115%

Uniformity
85%

Computer Compatibility
UXGA, WXGA, SXGA+, SXGA, XGA,
SVGA, VGA Resized, VESA, PC and
Macintosh Compatible

Video Compatibility
NTSC, PAL, SECAM, SDTV (480i),
EDTV (480p), HDTV (720p, 1080i/p)

Horizontal Scan Rate
15.3 to 91.1 KHz

Vertical Refresh Rate
25 to 85 Hz

Keystone Correction
±40° Vertical

Loop Through
Monitor: D-Sub 15-Pin VGA Output
Audio: Stereo Mini-Jack Output
(Functional in Both Normal and
Standby Modes)

Projection Lens
F= 2.4-2.66, f= 18.2-21.8mm,
1.2x Manual Zoom and Focus

User Controls
Complete On-Screen Menu
Adjustments in 23 Languages

I/O Connectors
HDMI, Two VGA-In, VGA-Out,
S-Video, Composite Video, Three
Stereo Audio-In, Stereo Audio-Out,
RJ45, RS-232 and USB

Security
Kensington® Lock, Security Bar and
Keypad Lock

Projection Method
Front, Rear, Ceiling Mount, Table Top

Weight
6.4 lbs (2.9kg)

Dimensions (W x H x D)
12.76" x 3.82" x 9.21"
(324 x 97 x 234 mm)

Noise Level (STD/Bright)
29dB/34dB

Operating Temperature
41 to 104°F (5 to 40°C), 80% Max
Humidity

Power Supply
AC Input 100-240V, 50-60Hz,
Auto-Switching

Power Consumption
255 Watts (Bright), 233 Watts (STD),
<1 Watt (Standby)

Warranty
3 Years Optoma Express
Replacement Service, 1 Year on
Lamp

Standard Accessories
AC Power Cord, VGA to VGA Cable,
Remote Control, Batteries for
Remote, USB Cable, Carrying Case,
Lens Cap, CD-ROM User's Manual,
Quick Start Card and Warranty Card

Optional Accessories
Wireless Dongle, Ceiling Mount,
HDMI Cable, VGA to Component
Cable, S-Video Cable, Composite
Video Cable, RS-232 Cable and
Panoview™ Series Screens

UPC
796435 41 159 6

Accessory Part Numbers
Lamp: BL-FP180D
Remote: BR-5030L
Mount: BM-5001U
Case: BK-4028
Wireless Dongle: BI-EXTGB