

DX608 Digital Projector

Delivering Style, Performance and High-Resolution Imagery

The Optoma DX-608 XGA digital projector is the perfect projector for a variety of environments. A powerful performer from boardrooms to classrooms, the DX-608 features 3000 lumens of brightness, extensive video and audio connectivity, and whisper quiet operation. The new Express On/Off feature eliminates long wait times, making the DX-608 operation-ready in seconds.



Features

- Ultra-bright **3000 lumens** for dazzling images in any environment
- Superb **2000:1 contrast ratio**
- **Express On/Off** feature powers on or off the projector in seconds
- Extensive **connectivity options**, including digital DVI with HDCP, four video and four audio sources
- **Innovative “Wind Tunnel” cooling** system delivers whisper-quiet operation with minimal light leakage
- **Fully featured remote mouse** with laser pointer
- **Photocatalysis (O2air™)** technology ensures air quality
- **Administrative password security system** prevents unauthorized usage & setting changes
- **Projector ID code** technology to identify and control by RS232 in a integration environment



Specifications

Brightness

3000 Lumens (Typical)

Resolution

Native XGA (1024 x 768)

Maximum Resolution

PC: SXGA+ (1400 x 1050)
Video: 720p, 1080i

Contrast Ratio

2000:1 (Full On/Full Off)

Lamp Life and Type

2000/3000 Hours (STD/ECO)
230W P-VIP

Display Type

Single 0.7" DDR DLP® Technology
by Texas Instruments

Throw Ratio

2.0 ~ 2.4:1 (Distance/Width)

Projection Distance

3.9' to 39' (1.2 to 12 m)

Image Size

30.75" to 300" (0.8 to 7.6 m)

Dimensions (W x H x D)

13.5" x 3.7" x 9.7"
(347 x 95 x 347 mm)

PC Compatibility

SXGA+, SXGA, XGA, SVGA, VGA
Compression; VESA standards;
PC and Macintosh Compatible

Video Compatibility

NTSC, PAL, SECAM,
HDTV (720p, 1080i),
EDTV (480i/p, 576i/p)

Projection Lens

F/2.4 ~ 2.6, f = 28 – 33.6mm,
1:2x manual zoom and focus

I/O Connections

DVI-D HDCP, Two VGA-In,
S-Video, Composite Video, USB,
Four Stereo Audio Input, One
Stereo Output, VGA-Out, RS-232,
Two IR Receivers

Uniformity

85%

Weight

7 lbs (3.15kg)

Operating Temperature

5 to 35°C, 80% max humidity

Storage Temperature

-20 to 60°C, 80% max humidity

Noise Level

30dB/28dB (STD/ECO)

Power Supply

100-240 volts, 50 to 60 Hz

Power Consumption

265W, <10W standby power

Standard Accessories

AC Power Cord, VGA to VGA
Cable, S-Video Cable, RS-232
Cable, Remote Control,
Batteries for Remote, Lens Cap,
Quick Start Guide, Warranty
Card and User's Manual

Optional Accessories

Bering Ceiling Mount, 15-pin
to 3 RCA Component/HDTV
Adapter, DVI to HDMI Adapter,
GrayWolf™ Series Screen

Warranty

1 Year Limited Parts and Labor,
90 Days on Lamp

UPC

796435 21 816 4