

## SRX-R510P

4K digital cinema projection system for small screens



### Key Feature

#### True 4K images with premium-quality lens and integrated media block

The SRX-R510P with 4096 x 2160 pixel resolution that's four times the resolution of 2K and HD. The top-quality F2.5 large aperture lens employs ELD (Extra Low Dispersion) glass to create finely-detailed 4K images. Unlike other projection systems that combine a 2K lens and 4K media block, the SRX-R510P combines a set of 4K SXRD panels plus 4K lens and media block for true 4K images at the highest resolution.

#### Give audiences the immersive thrill of Sony 4K for small cinema screens.

Building on the success of the acclaimed SRX-R515P, the SRX-R510P brings a true Sony 4K digital cinematic experience to cost-conscious smaller theatres.

Teaming superb 4K picture quality with affordable running costs, the SRX-R510P shares the same compact body, integrated media block and SXRD optical engine as the SRX-R515P.

Also derived from the SRX-R515P, the resilient 4-lamp High Pressure Mercury (HPM) array delivers a 9,000 lumen light output from four individually-replaceable projection lamps.

There's a choice of high quality 2D projection lenses to suit different-sized auditoria. And it's simple upgrading to smooth, immersive 3D with the addition of an easy-to-fit 3D lens/filter option.

The easy-to-use projector features an intuitive 15-inch touch panel user interface, and can also be controlled remotely via a networked PC and web browser.



## Features

### Easy-on-the-eye 3D

Sony's unique dual lens system displays 3D movies at their native 2K resolution. Left and Right eye images are projected simultaneously to achieve crisp 3D images, without the problems associated with 'triple flash' image alternation systems.

### High contrast for lifelike images

The SXRD optical engine of the SRX-R510P delivers an extremely high contrast ratio more than 4,000:1, assuring lifelike images with sparkling highlights and deep, dark blacks.

### Cost-effective HPM lamp array offers safe, easy lamp replacement

An array of four High Pressure Mercury (HPM) lamps offers high brightness, resilience and durability. Projector operation is maintained even if a lamp fails during a performance. Lamp replacement is safe and easy, while contributing to reduced overall running costs.

### High brightness projection on screens up to 10m wide

The SRX-R510P offers a generous brightness of 9,000 lumens (with 450W lamps), optimised for small cinema screens up to 10m wide (with 450W lamps, for 2D projection).

### Convenient installation

The projector can be conveniently installed in smaller projection booths. The body structure also forms a security enclosure specifically developed to comply with the FIPS-140/2 physical security and anti-tamper requirements specified by the DCI.

### High speed content ingest

The SRX-R510P features high network transfer speeds via USB 3.0, assisting with streamlined show scheduling for busy theatre managers.

### Larger size GUI and remote control of screen management system software

The large 15-inch touch screen Graphical User Interface (GUI) is compatible with Sony's Theatre Management System that simplifies projector set-up, content management and creation of a complete show schedule. Remote operation is also supported via a networked PC and web browser.

### Flexible 3D and alternative content via HDMI

Two standard HDMI inputs allow 3D playback, as well as simplifying projection of alternative content such as live video or Blu-ray Disc playback.

## SRX-R510P

Give audiences the  
immersive thrill of Sony 4K

### SRX-R510P & Server



New touch panel monitor and  
graphical user interface

New light source system  
(4x high pressure mercury lamps)

New optical engine

New Integrated Media Block

New server

## Specifications

SRX-R510P	
<b>Projector</b>	
Display Device	3 x 1.48 inch 4K SXRD
Lamp	4 x 450W High Pressure Mercury (HPM) lamps or 4 x 330W High Pressure Mercury (HPM) lamps
Light output (Average)	9,000 lm (centre) (450W lamp) / 6,600 lm (centre) (330W lamp)
Contrast ratio	more than 4,000:1
<b>Interface</b>	
Video Input	HDMI x 2
Audio Output	Unbalance 8ch 24bits, 48/96kHz, Linear PCM AES/EBU 16ch 24bits, 48/96kHz, Linear PCM
Ingest	USB 3.0 x 2 CRU Data Port Slot x 1
System Control	GPIOs x 8 / GPOs x 16 USB 2.0 x 1 (for UPS control) RS-232C x 1 (for Audio Processor Control <sup>*1</sup> )
Network	Gigabit Ethernet x 2
<b>Storage and Playback</b>	
Storage	4TB Modified RAID6
Playback (JPEG2000)	4K 2D: 24P 2K 2D: 24/25 <sup>2</sup> /29.97 <sup>2</sup> /30 <sup>2</sup> /48/60P 2K 3D: 24/29.97 <sup>2</sup> /30 <sup>2</sup> /48/60P
Playback (Others)	MPEG2 <sup>3</sup> MP@HL YUV4:2:0/4:2:2 8bit Bit rate 80Mbps (max) 1920 x 1080 23.09P/24P/25P
<b>General – Projector</b>	
Dimensions (WxHxD)	548 x 634 x 1119 mm (21.5 x 24.9 x 44 inches) <sup>4</sup>
Mass	Approx. 145kg (319.6 lb) <sup>5</sup>
Power Requirement	AC 200 to 240V, 50-60Hz, Single-phase, 21.5A to 18A
Power Consumption	450W lamp: Max. 4.3kW 330W lamp: Max. 3.2kW
Exhaust Airflow	450-550CFM
<b>General – Server</b>	
Dimensions (WxHxD)	482 x 131 x 560 mm (18.9 x 5.1 x 22 inches)
Mass	Approx. 24kg (52.9 lb)
Power Requirement	AC 100 to 240V, 50-60Hz, Single-phase, 2.2A to 1.0A
Power Consumption	Max. 240W
<b>General – Touch panel monitor</b>	
Dimensions (WxHxD)	350 x 310 x 57 mm (13.7 x 12.2 x 2.2 inches)
Mass	Approx. 3.6 kg (7.9 lb)
Power Requirement	DC12V, 1A, Adaptor: AC 100 to 240V, 50-60Hz, Single-phase
Power Consumption	Max. 12W
<b>General – Common</b>	
Operating Temperature	5°C to -35°C (41°F to 95°F)
Operating Humidity	35% to 85% (no condensation)
Storage Temperature	-20°C to +60°C (12°F to 140°F)
Storage Humidity	10 to 90%
<b>Other</b>	
Safety Regulation	<b>Digital Cinema Projector SRX-R510P</b> VCCI Class A, UL 60950-1, CSA C22.2 No.60950-1, FCC/IC Class A Digital Device, IEC 60950-1, EN 55022 Class A + EN 55024, EN 61000-3-11 + EN 61000-3-12, AS/NZS CISPR22 (EN 55022) Class A <b>Digital Cinema Server XCT-S10</b> VCCI Class A, 電気通信事業法, UL 60950-1, CSA C22.2 No.60950-1, FCC/IC Class A Digital Device, IEC 60950-1, EN60950-1, EN 55022 Class A + EN 55024, EN 61000-3-2 + EN 61000-3-3, AS/NZS CISPR22 (EN 55022) Class A <b>Touch Panel Monitor LKRA-007</b> VCCI Class A, FCC/IC Class A Digital Device, EN 55022 Class A + EN 55024, AS/NZS CISPR22 (EN 55022) Class A
Supplied Accessories	<b>Digital Cinema Projector SRX-R510P</b> Keys for removing panels (5), Safety regulations (1), TPC arm (1 set), Cable clasper (2) <b>Digital Cinema Server XCT-S10</b> Feet (1 set), PCI express cable (2m) (1), Ethernet cable (2m) (1) <b>Touch Panel Monitor LKRA-007</b> AC adaptor (1), VGA cable (1), USB cable (1) <b>Sony supplies the first set up lamps with every Projector, this is included in the Projector price.</b>

SRX-R510P			
<b>2D Lens</b>	LKRL-Z511	LKRL-Z514	LKRL-Z519
Throw Ratio	1.05-1.75	1.35-2.34	1.80-4.00
V shift	+/- 35%		
H shift	+/- 7%		
Dimensions (WxHxD)	256 x 315 x 429 mm (10 x 12.4 x 16.8 inches)	256 x 315 x 454 mm (10 x 12.4 x 17.8 inches)	256 x 315 x 413 mm (10 x 12.4 x 16.2 inches)
Mass	14.5kg (31.9 lb)	14kg (30.8 lb)	13kg (28.6 lb)
<b>Lamp</b>	LKRM-U450	LKRM-U330	
Dimensions (WxHxD)	89 x 122 x 148 mm (3.5 x 4.8 x 5.8 inches)		
Mass	510 g (1.1 lb)		

Supported signals for HDMI inputs		
<b>Video</b>		
Resolution	Frame Rate	
720 x 480	59.94P / 59.94I / 60I / 60P	
720 x 576	50I / 50P	
1280 x 720	50P / 59.94P / 60P	
1920 x 1080	23.98P/24P / 50I / 50P / 59.94I / 60I / 59.94P / 60P	
2048 x 1080	23.98P / 24P / 60P	
<b>Computer</b>		
Resolution	Frame Rate	
VGA (640 x 480)	60	
XGA (1024 x 768)	60	
UXGA (1600 x 1200)	60	
WUXGA (1920 x 1200)	60	
<b>3D</b>		
3D structure	Resolution	Frame Rate
Frame Packing	1280 x 720	50P / 59.94P/60P
	1920 x 1080	23.98P/24P
Top & Bottom	1280 x 720	50P / 59.94P/60P
	1920 x 1080	23.98P/24P / 50P / 59.94P/60P
Side by Side	1280 x 720	50P / 59.94P/60P
	1920 x 1080	50I / 50P / 59.94I / 59.94P/ 60I / 60P
Dual Input <sup>*6</sup>	1280 x 720	50P / 59.94P/60P
	1920 x 1080	23.98P/24P / 50I / 50P / 59.94I / 59.94P/ 60I / 60P

\*1 The tested audio processors are listed below.  
Dolby CP650 (ver. 1.2.3.0, ver. 2.2.5.3, ver. 2.3.5.3, ver. 2.3.6.3, ver. 2.3.6.6)  
Dolby CP750 (ver. 1.2.8.3) \* You can also control the CP750 via network.

\*2 We don't support watermarking on these frame rate.

\*3 We don't support watermarking and handling subtitle file on MPEG2 content.

\*4 It includes lens shift block and adjustable feet and excludes touch panel monitor and projecting parts of the unit such as status light and chimney.

\*5 It excludes lamps, lens, and touch panel monitor.

\*6 Each L and R image is separately fed to two HDMI input.

For full features visit [www.pro.sony.eu/dcinema](http://www.pro.sony.eu/dcinema)

© 2013 Sony Corporation. All rights reserved. Reproduction in whole or in part without permission is prohibited. Features and specifications are subject to change without notice. All non-metric weights and measurements are approximate. Sony and make.believe are trademarks of Sony Corporation. All other trademarks are the property of their respective owners.

Distributed by

Professional Solutions Europe is the leading supplier of AV/IT solutions to businesses across a wide variety of sectors including, **Media and Broadcast, Video Security and Retail, Transport & Large Venue markets**. It delivers products, systems and applications to enable the creation, manipulation and distribution of digital audio-visual content that add value to businesses and their customers. With over 25 years' experience in delivering innovative market-leading products, **Professional Solutions Europe** is ideally placed to deliver exceptional quality and value to its customers. **Sony's Professional Services** division, its systems integration arm, offers its customers access to the expertise and local knowledge of skilled professionals across Europe. Collaborating with a network of established technology partners, Professional Solutions Europe delivers end to end solutions that address the customer's needs, integrating software and systems to achieve each organisations' individual business goals. For more information please visit [www.pro.sony.eu](http://www.pro.sony.eu)

HCI\_SRX-R510P\_Datasheet\_J2448\_UK\_27/11/2013

**SONY**  
make.believe