

PT-RDQ10 Series

1-Chip DLP™ Projectors

AVAILABLE FROM OCTOBER 2021

1-Chip DLP™ 4K Projectors Create Captivating and Immersive Entertainment Experiences



Black Models



White Models



PT-RDQ10 Series			
	PT-RDQ10	PT-RDQ90	PT-RDQ80
Light Output	10,000 lm*1	9,000 lm*1	8,000 lm*1
Resolution	4K (3840 x 2160 pixels)*2		
Aspect Ratio	16:9		

• Captivating 4K Images and Vibrant Colors Deepen Immersion

PT-RDQ10 Series harnesses original 1-axis pixel-shifting technology, Smooth Pixel Drive, and 0.66" DMD to produce crisp, smooth, and richly detailed 4K (3840 x 2160, 16:9) images. Rich Color Enhancer boosts vibrant red expression while improved black-border adjustment enhances uniformity for seamless edge-blends on curved screens.

• Flexibility and Expandability Simplify Integration

Compatibility with ET-DLE020 Ultra-Short-Throw Zoom Lens enhances application flexibility. Optional SLOT NX interface boards, such as 12G-SDI and DisplayPort™, streamline integration while preactivated Geometry Manager Pro™3 upgrade kits and Remote Preview Lite™4 simplify adjustment.

• Reliable Low-Maintenance Operation in an All-New Compact Body

Despite its expanded features, PT-RDQ10 Series retains the same compact dimensions as our 1-Chip DLP™ models in an all-new cabinet. Liquid-cooling system inherited from our 3-Chip DLP™ models supports hermetic optical-block sealing, achieving up to 20,000-hour⁵ maintenance-free operation, while laser failover circuitry and Backup Input insure against interruptions.

Specifications (Tentative)

Model	PT-RDQ10	PT-RDQ90	PT-RDQ80
Projector type	1-Chip DLP™ projector		
DLP™ chip	Panel size	16.8 mm (0.66 in) diagonal (16:9 aspect ratio)	
	Display method	DLP™ chip x 1, DLP™ projection system	
	Number of pixels	2716 x 1528 pixels (Images cannot be displayed at this resolution)	
Light source	Laser diodes		
Light output*1 *2	10,000 lm	9,000 lm	8,000 lm
Time until light output declines to 50 %*3	20,000 hours (NORMAL/QUIET)/24,000 hours (ECO)		
Resolution	4K (3840 x 2160 pixels) (With Smooth Pixel Drive)		
Contrast ratio*1	10,000:1 (Full On/Full Off) (When [PICTURE MODE] is set to [DYNAMIC] and [DYNAMIC CONTRAST] is set to [3]. HDMI signal input)		
Screen size (diagonal)	1.52–15.24 m (60–600 in) with ET-DLE060/ET-DLE088/ET-DLE158/ET-DLE178**/ET-DLE258, 2.54–10.16 m (100–400 in) with ET-DLE020, 16:9 aspect ratio		
Center-to-corner zone ratio*1	90 %		
Lens	Powered zoom (throw ratio 1.60–2.58:1), powered focus (for supplied lens; optional lenses also available)		
Lens shift (From the origin point of the lens mounter)	Vertical	±60 % with ET-DLE088/ET-DLE158/ET-DLE178**/ET-DLE258 (±49 % with ET-DLE060, ±59 %, -40 % with ET-DLE020) (powered)	
	Horizontal	±25 % with ET-DLE088/ET-DLE158/ET-DLE178**/ET-DLE258 (±19 % with ET-DLE060, ±24 % with ET-DLE020) (powered)	
Keystone correction range	TBD		
Installation	Ceiling/floor, front/rear, free 360-degree installation		
Terminals	HDMI IN	HDMI 19-pin x 2 (Compatible with HDCP 2.3, Deep Color, 4K/60p signal input)	
	MULTI PROJECTOR SYNC IN	BNC x 1	
	MULTI PROJECTOR SYNC OUT	BNC x 1	
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)	
	SERIAL OUT	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)	
	REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control	
	REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control (for wired remote control)	
	REMOTE 2 IN	D-sub 9-pin (female) x 1 for external control (parallel)	
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection (video/network/serial control) (HDBaseT™ compliant), 100Base-TX (Compatible with PLink™ [Class 2], Art-Net, HDCP 2.3, Deep Color, 4K/60p signal input)	
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX (Compatible with PLink™ [Class 2], Art-Net)	
	USB	USB Connector (Type A) x 1 for Cloning/Wireless Module (Output 5 V/500 mA)	
	DC OUT	USB Connector (Type A) x 1 (Output 5 V/2 A)	
	Expansion Slot	Open slot for SLOT NX compatible interface board	
Power supply	AC 100–240 V, 50/60 Hz		
Power consumption	TBD	TBD	TBD
Cabinet materials	Molded plastic		
Operation noise*1	39 dB (NORMAL/ECO) [TBD] / 35 dB (QUIET) [TBD]	37 dB (NORMAL/ECO) [TBD] / 33 dB (QUIET) [TBD]	35 dB (NORMAL/ECO) [TBD] / 31 dB (QUIET) [TBD]
Dimensions (W x H x D)*5	498 x 200 x 538 mm (19 19/32" x 7 7/8" x 21 3/16") excluding lens [TBD]		
Weight*6	Less than 25 kg (55.1 lbs) excluding lens [TBD]		
Operating environment	Operating temperature: 0–45 °C (32–113 °F)**; operating humidity: 10–80 % (no condensation)		
Applicable software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Geometry Manager Pro, Smart Projector Control for iOS/Android™		

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 When [PICTURE MODE] is set to [DYNAMIC] and [LIGHT POWER] is set to [NORMAL]. *3 Around this time, light output will have decreased to approximately 50 % of its original level ([PICTURE MODE]: [DYNAMIC], [DYNAMIC CONTRAST] set to [3], temperature 35 °C (86 °F), elevation 700 m (2,297 ft) of particulate matter). Estimated time until light output declines to 50 % varies depending on environment. *4 ET-DLE178 is equivalent of supplied lens. Availability of ET-DLE178 varies depending on country. *5 With legs fully retracted, excluding lens and protruding parts. *6 Average value. May differ depending on the actual unit. *7 When using the projector at an altitude lower than 2,700 m (8,858 ft) above sea level, and the operating environment temperature becomes 30 °C (86 °F) or higher, the light output may be reduced to protect the projector. When using the projector at an altitude between 2,700 m (8,858 ft) and 4,200 m (13,780 ft), and the operating environment temperature becomes 25 °C (77 °F) or higher, the light output may be reduced to protect the projector. *8 When optional AJ-WM50 Series wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F).

Optional Accessories

• Zoom Lens

ET-DLE020 (0.277–0.296:1) / ET-DLE060 (0.594–0.793:1) / ET-DLE088 (0.782–1.10:1) / ET-DLE158 (1.08–1.62:1) / ET-DLE178* (1.60–2.58:1) / ET-DLE258 (2.55–3.82:1)
* ET-DLE178 is equivalent of supplied lens. Availability of ET-DLE178 varies depending on country.
Note: ET-DLE158 and ET-DLE258 will be available from January 2022.

• Ceiling Mount Bracket

ET-PKD130H* (with 6-axis adjustment for high ceilings)
ET-PKD120H* (for high ceilings)
ET-PKD120S* (for low ceilings)
* ET-PKD130H/PKD120H/PKD120S used in combination with ET-PKD130B (sold separately).

• Attachment for Ceiling Mount Bracket

ET-PKD130B

• Interface Boards

Interface Board for 12G-SDI
(Input x 2, Input/Output x 2)
ET-MDN12G10
Interface Board for 12G-SDI Optical
(Input x 1, Input/Output x 1)
ET-MDNFB10
Interface Board for HDMI® (Input x 2)
ET-MDNHM10
Interface Board for DVI-D (Input x 2)
ET-MDNDV10
Interface Board for DisplayPort™
(Input x 2)
ET-MDNDP10

• DIGITAL LINK Switcher

ET-YFB200G*
* Not compatible with 4K signals.

• Digital Interface Box

ET-YFB100G*
* Not compatible with 4K signals.

• Wireless Module

AJ-WM50 Series*
* The suffix at the end of the model number is omitted.
Operating temperature: 0–40 °C (32–104 °F). Product availability may vary by country or region.

• Early Warning Software

ET-SWA100 Series*
* Part number suffix may differ depending on the license type.

• NFC Upgrade Kit

ET-NUK10*
* Product availability may vary by country or region.

• Wireless Presentation System PressIT

TY-WPS1 (basic set)
Visit panasonic.net/cns/prodisplays/pressit for more information.