SPECIFICATIONS	MX825ST			
Projection System	DLP®			
Native Resolution	XGA(1024X768)			
Brightness	3300AL			
Contrast Ratio	12000:1			
Display Color	1.07 Billion Colors			
Lens	F/#=2.6 f=6.9mm			
Aspect Ratio	Native 4:3 (5 aspect ratio selectable)			
Throw Ratio Clear Image Size / Maximum Image Size	0.61 60"~120" / 120"			
Zoom Ratio	Fixed			
Lamp Type	200W			
Lamp Mode	5000/10000/10000/15000 hours			
(Normal/Economic/SmartEco/LampSave)				
Keystone Adjustment	1D, Vertical +/- 30 degrees			
Projection Offset	15%±2.5% (Full-Height)			
Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x	1200) *RB-Reduced Blanking"		
Horizontal Frequency Vertical Scan Rate	15K~102KHz 23~120Hz			
		180i 180n 576i 567n 700n	10801 1090-	
Compatibility	HDTV Compatibility 3D Compatibility (Please refer to User's Manual for detailed support timing.)"	480i, 480p, 576i, 567p, 720p, 1080i, 1080p Frame Sequential: Up to 720p Frame Packing: Up to 24 Hz 1080p Side by Side Half: Up to 60Hz 1080p Top Bottom: Up to 60Hz 1080p		
Interface	Computer in (D-sub 15pin)	x 2 (Share with component)		
	Monitor out (D-sub 15pin)	x 1		
	Composite Video in (RCA)	x 1		
	S-Video in (Mini DIN 4pin)	x 1		
	НДМІ	x2 (1 share with MHL)		
	Audio in (Mini Jack)	x2		
	Audio out (Mini Jack)	x 1		
		x 1		
	Audio L/R in (RCA)			
	Speaker	10Wx 1		
	USB (Type A)	x1 (power only 5V/1.5A)		
	USB (Type Mini B)	x1 (Download & page/down)	x1 (Download & page/down)	
	RS232 (DB-9pin)	x 1		
	LAN (RJ45)	x 1		
Dimensions	Dimensions(W x H x D)	296 (W)*239(D)*120(H) mm		
	Weight	2.6 Kg (5.7 lbs)		
Power	Power Supply	AC 100 to 240 V, 50/60 Hz		
	Power Consumption	260W(typical), Standby<0.5W, Network standby<2W		
Audible Noise (Normal/Economic)	33/29 dBA (Normal/Economic mode)			
On-Screen Display Languages	Arabic/ Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/ Japanese/ Korean/ Norwegian /Persian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese/ Vietnam (30 languages)			
Picture Modes	Bright / Presentation / sRGB / Cinema /	Bright / Presentation / sRGB / Cinema / (3D) / User 1 / User 2		
Accessories	Standard Optional			
	Remote Control w/ Battery RCE013, RCE013J (for J sku)	PointWrite	PW02	
	Power Cord (by region)	FingerTouch	PT12	
Accessories				
Accessories	User Manual CD	Spare Lamp Kit	5J.JGP05.001	
Accessories	User Manual CD Quick Start Guide	Spare Lamp Kit Wall Mount	5J.JGP05.001 WM06G3	

*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

MX825ST Digital Projector

- SmartEco Power Saving Technology
- 0.61 Short Throw Ratio
- Designed for Education & IWB
- Blu-ray Full HD 3D support
- PointWrite Interactive Solution Compatible









