PJD5351

LIGHT, BRIGHT AND VERSATILE DLP PROJECTOR

WITH EXTREME SHORT-THROW LENS

Short distance - big presentation

The powerful PJD5351 sets the stage for a new generation of versatile projectors equipped with BrilliantColor™ technology and an extreme short-throw ratio – producing a 60" image at a distance of only 1.1m away. With its short-throw lens, the PJD5351 saves space by allowing you to place it at the front of your table and still display large, crisp images. Weighing in at just 2.5kg with 2500 ANSI lumens and a 2400:1 contrast ratio (with DCR), it's easy to give multimedia lessons in the classroom or dynamic presentations in the boardroom. Multiple preset presentation modes, an increased 40 degree digital vertical keystone correction and digital zoom ensure the best possible image regardless of location. With up to 4000 hours of lamp life*, low-cost replacement lamps, filter-less design and a non-degrading DLP® light engine, the PJD5351 has one of the lowest total cost of ownership ratios in the industry.



Versatile presentations anywhere

> Short-throw lens for large, stunning images in small spaces
The short-throw lens enables large images to be projected from short
distances in small rooms. A screen size of 1.5m is possible from just 1.1m

> Advanced connectivity

In addition to standard connectors, this projector provides two RGB inputs to easily switch between presenters and an additional RGB output to connect to an ecxternal monitor.

> Bright in virtually any setting

Packs 2,500 ANSI lumens in just 2.5kg, and with a high 2400:1 contrast ratio (with DCR), your presentations are guaranteed to be vibrant even in the brightest office environment.

> BrilliantColor™ technology

Latest BrilliantColor™ Technology delivers stunning all-digital clarity with life-like color, sharp graphics and outstanding video. The sophisticated 6-segment color wheel enriches the yellow colour performance that is key to accurate and vivid colour reproduction.

> Eco-mode extends lamp life

Extend the life of your lamp up to 4000 hours* and reduce noise output to a whisper quiet 27db.

> Off-to-Go feature

The direct-off feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects the lamp from sudden power blackouts.













VIEWSONIC

PRODUCTS, PROGRAMS, AND SERVICES



PJD5351



PORTABLE VERSATILE DLP PROJECTOR







Optional Accessories

>Replacement lamp RLC-047
>Universal ceiling mount kit WMK-018
>Wireless G presentation gateway WPG-150
>3 year extended lamp warranty LSWP3

Projection Distance 4:3 Screen		Screen Size (diagonal) 4:3 Screen	
m	feet	m	inch
0.7	2.3	1.0	40
1.1	3.6	1.5	60
1.5	4.9	2.0	80
1.8	5.9	2.5	100
2.8	9.2	3.8	150
3.2	10.6	4.6	180







ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

DISPLAY	Туре	0.55" Digital Micromirror Device (DLP™)
	Resolution	XGA 1024x768 (Native) / SXGA 1280×1024 (compressed)
	Lens	Fixed zoom/ manual optical focus
	Keystone	Vertical digital keystone correction: +/- 40 degrees
	Display Size (diagonal)	40"-180" / 1.0m - 4.6m
	Throw Distance	0.75 - 3.5m
	Throw Ratio	0.9:1
	Lamp	189 watt
	Lamp Life (Normal / Eco Mode)	3000 / 4000 hours*
	Brightness	2500 Lumens
	Contrast Ratio	2400:1 (with DCR)
	Aspect Ratio	4:3 (native) & 16:9
	Color Gamut	85 % NTSC 1931 CIE
AUDIO	Speaker	5W×1
INPUT SIGNAL	Computer and video	NTSC M (3.58 MHz), 4.43MHz, PAL (B, D, G, H, I, M, N, 60), SD 480i and
		576i (24fps, 25fps and 30fps), ED 480p and 576p (24fps, 25fps and 30fps),
		HD 720p, 1080i (24fps, 25pfs and 30fps)
	Frequency	Fh: 30-100 KHz, Fv: 50-87 Hz
COMPATIBILITY	PC	VGA to SXGA
	Mac	Up to 1280×1024 (may require Mac Adapter)
CONNECTOR	RGB Input	2 × 15-pin mini D-sub
	Component	2 × 15-in mini -D-Sub (sharer with RGB)
	RGB Output	1 × 15-pin mini D-sub
	Composite Input	1 × RCA jack
	S-Video Input	1 × 4-pin mini-DIN
	Audio Input	1 × 3.5mm mini jack
	Audio Output	1 × 3.5mm mini jack
	Control	1×RS-232 (8 Pin Mini-Din)
POWER	Voltage	90~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	242W (Typical) / <5W (Stand-by mode)
LANGUAGE		English, French , German, Italian, Spanish, Russian, Traditional Chinese,
		Simplified Chinese, Japanese, Korean, Swedish, Dutch, Turkish, Czech,
		Portuguese, Thai, Polish, Finnish
CONTROLS	Keypad	Standby/On, input, menu
00.1111022	OSD	Display: Screen color, aspect ratio, keystone, position, phase, H. size, digital zoom
		Picture: Preset mode: brightest, standard (Video) ,daylight, ViewMatch
		(PC), cinema, user 1/user 2, brightness, contrast, color, tint, sharpness,
		BrilliantColor™, color temp., save settings)
		Source: Quick auto search
		System setting (Basic): Language , projector position, auto power off, blank
		timer, panel key lock, timer controller, splash screen
		System setting (Advanced): Quick cooling, high altitude mode, DCR, active
		VGA out, audio settings, menu settings, closed caption, lamp settings,
		security setting, reset all settings
		Information: Current system status (source, preset mode, resolution, color
		system, equivalent lamp hour)
		system, equivalent lamp nour)

0°C-40°C (32°F-104°F)

30dB / 26dB

2.5 kg (5.5lb)

10% - 90% (non-condensing)

0~1,800m (6000ft), operational up to 3,048m (10000ft)

CB, ROHS, WEEE, UL/cUL, FCC-B, ICES-003, IRAM (Argentina), NOMPSB, C-tick, EK, CE, TUV/GS, GOST-R, Hygienic, SASO UKrSEPRO, CCC

ViewSonic projector, power cable, VGA cable, remote control with batteries,

lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide), soft case

264 × 96.4 × 225 (mm) / 10.4 × 3.8 × 8.86 (inch)

 $380 \times 324 \times 191 \text{ (mm)} / 14.9 \times 12.8 \times 7.5 \text{ (inch)}$



OPERATING

CONDITIONS

NOISE LEVEL

DIMENSIONS

REGULATIONS

WARRANTY

PACKAGE CONTENTS

(W x H x D) WEIGHT Temperature

Normal / Eco Mode

Humidity

Altitude

Physical

Net

3-year limited warranty on parts, 1-year limited warranty on lamp $$\operatorname{\textsc{Rev}}.1.0$$

