

## Key Features

- LED technology with 30,000 hours lifespan
- Instant power on/off for efficient use
- 3,000 LED Lumens
   offering bright images
   in any environment
- 360° projection for versatile application
- Convenient projector software updates via USB connection



## Product **Description**

The LS500W is ViewSonic's first lamp-free, 3,000 LED Lumens high brightness WXGA projector for business and education. Adopting industry-leading LED technology, it frees users from frequent lamp replacement and toxic mercury for a safer and greener environment, offering phenomenal lifespan of 30,000 hours and true-to-life colours with 125% Rec.709. Give light to your presentations effortlessly with efficient instant power on/off and 360° tilt angle projection for flexible setup in small-to-medium sized meeting rooms/classrooms.



- 1. Keypad
- 2. Power Button
- 3. Front IR
- 4. Lens
  5. LED Indicator
- 6. Zoom/Focus Ring
- 7. Audio In

- 8. Audio Out
- 9. Monitor Out
- 10. RS-232
- 11. Computer In
- 12. HDMI
- 13. USB Type A(5V/2A, Service)

**SPECIFICATION OTHERS** Native Resolution: 1280x800 100-240V+/- 10%, Power Supply Voltage: 50/60Hz(AC in) DMD Type: DC3 Normal: Brightness: 3000 (LED Lumens) 156WStandby: Power Consumption: <0.5W 3000000:1 Contrast Ratio: Operating Temperature: 0~40°C Display Colour: 1.07 Billion Colours Net Weight: 2.45kg LED Light Source Type: Dimensions (WxDxH) with 293x221x115mm Light Source Life (hours) up to 30000 Adjustment Foot: with Normal Mode: English, French, **RGB LED** Lamp Watt: Spanish, Thai, Korean, German, F=2.56-2.68. Lens: Italian, Russian, f=22-24.1mm Swedish, Dutch, Polish, Czech, 100%+/-5% Projection Offset: T-Chinese, OSD Language: S-Chinese, Throw Ratio: 1.55-1.70 Japanese, Turkish, Portuguese, Finnish, 1.1X Optical Zoom: Indonesian, India, Arabic, Vietnamese, Digital Zoom: 0.8x-2.0x Greek, Hungarian. Total 24 languages 30"-300" Image Size: Throw Distance: 1m-10.98m(100"@3.34m) STANDARD ACCESSORY +/- 40° (V) Power Cord: Keystone: VGA Cable: Audible Noise (Normal): 30dB Remote Control: Audible Noise (Eco): 26dB QSG: 16ms Yes Input Lag: VGA(640 x 480) to **OPTIONAL ACCESSORY** Resolution Support: FullHD(1920 x 1080) Wall/Ceiling Mount: PJ-WMK-007 480i, 480p, 576i, 576p, **HDTV** Compatibility: Carry Bag: PJ-CASE-008

HDTV Compatibility: 4801, 4809, 3761, 3769, 720p, 1080i, 1080p

Video Compatibility: NTSC, PAL, SECAM

Horizontal Frequency: 15K-102KHZ Vertical Scan Rate: 23-120HZ

INPUT

Computer in (share with component):

HDMI: 1(HDMI 1.4/ HDCP

1

1.4)

Audio-in (3.5mm):

OUTPUT

 Monitor out:
 1

 Audio-out (3.5mm):
 1

 Speaker:
 2W

USB Type A (Power): 1 (5V/2A)

CONTROL

RS232 (DB 9-pin male): 1