




P1266i PROJECTOR

DLP Technology – Hi definition wireless

P1266i wireless projector offers flexible connections, including WiFi wireless, Ethernet and conventional cables. Not only the capability of projection from a PC or a DVD player, furthermore, the world leading MobiShow technology even allows the projection from a WiFi smart phone.

Why P1266i Projector?

- Wireless 802.11b/g wireless technology
- Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
- Contrast Ratio 2700:1
- Brightness 2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 32.0' (9.8m)



empowering technology



SmartFormat

Technical Specifications

Model Name	P1266i
Resolution	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), WSXGA+ (1,680 x 1,050)
Computer Compatibility	IBM PC and Compatibles, Apple Macintosh and iMac (Wireless and Ethernet function exclusive), and VESA Standards WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	2700:1
Displayable Colours	134 Million Colors
Brightness	2,700 ANSI Lumens (Standard), 2,160 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.66, f = 18.17mm ~ 21.81mm / 1:1.2 Manual Zoom and Manual Focus
Projection Screen Size	26" (65cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 32.0' (9.8m)
Throw Ratio	62"@2m (1.60 ~ 1.92:1)
Horizontal Scan Rate	31.5 ~ 100 kHz
Vertical Scan Rate	50 ~ 85 Hz
Lamp Life	3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 2 watts Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	285 Watts (Operation), 5 Watts (Standby, wireless off)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	30 dBA (Standard mode), 25 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 1
Output Interface	Analog RGB (D-sub) x 1
Control Interface	USB (Type B) x 1, RS232 (Mini DIN) x 1
Wireless / Network Interface	Yes (Windows XP above PC & Windows Mobile 5.0 above smart phone projection) 802.11b/g wireless technology, Ethernet port (RJ45) x 1, Wireless antenna connector (SMA) x 1
Weight and Dimensions	5.7 lbs (2.6 Kg) / 269 x 206 x 96 mm (10.6" x 8.1" x 3.8")
Compliance	C-Tick (AS/NZS 60950)
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.

¹ Specifications vary depending on model.