



- → Non-driver wireless projection supports iOS\* and Android™ devices
- → Compatible with USB webcams
- → Capable to run videoconference apps directly
- → Auto Sound/Picture Mode Switch
- → AES128 Encryption, Support WPA2

















Display Projection System Single DLP DMD type 0.47" 1080P Native Resolution Full HD (1920 x 1080) Brightness 3400 ANSI Lumens Contrast Ratio\*\*

Display Colour 30 Bits/1.07 Billion Colours Aspect Ratio Native 16:9 (5 aspect ratios selectable) Light Source Lamp

Light Source Life \*\*\* (Normal/Eco/SmartEco/Lamp Save) 4000/10,000/15,000/15,000 hours

Optical

Throw Ratio 1.13-1.47 Zoom Ratio 1.3x Lens Shift NΑ

Keystone Correction Auto ID, Vertical ± 40 degrees

105.0% Projection Offset 40"-200" Projection Size Audio

Built-In Speaker

5W x2

Smart System

CPU Whiskey Lake: Celeron-4205U eMMC 64GB TLC Storage Type DDR4-2400 SO-DIMM 4GB RAM Type

Windows® 11 OS System

Special Feature

Security bar, Kensington anti-theft lock slot Security

Built-in Windows® system, Wireless Projection, USB webcam compatible, Video Conference Meeting compatible, AES128, Auto Picture & Sound Mode Switch, D Auto Keystone Feature

Compatibility

VGA (640 x 480) to WUXGA\_RB (1920 x 1200) Resolution Support

Horizontal Frequency 15K-102KHz Vertical Scan Rate 23-120 Hz

HDTV Compatibility 480i, 480p, 576i, 567p, 720p, 1080i, 1080p

NTSC, PAL, SECAM, SDTV, (480i/576i), EDTV (480p/576p), HDTV (720p, 1080i/p 60Hz) Video Compatibility

Power Consumptions (Max/Normal/Eco) 350W/340W/280W Stand-by Power Consumption Normal < 0.5W Power Supply 100-240V AC

**Dimension and Weight** 

380 x 127 x 263mm Product Dimensions (WxHxD) Product Weight 4.2kg ± 200gr

**Operation Condition** 

Noise Level (Normal/Eco) 32/28 dBA Operating Temperature 0 - 40°C

Accessories

Accessories (Standard) QSG (4JJPT01.001), Remote control (5J.JLR06.001), AAA Battery x2, VGA cable (1.5m), Power cord (1.8m), Warranty card (by Region) Spare lamp kit (5J.JPT05.001), 3D Glasses (5J.J9H25.002), Ceiling mount (5J.JAM10.001), Wi-Fi dongle (5J.JPT28.001), WDC10, WDC20 Accessories (Optional)


A rabic/Bulgarian/Croatian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Italian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Czech/Danish/Dutch/English/Farsi/Finnish/French/German/Greek/Hindi/Hungarian/Indonesian/Czech/Danish/DanOn Screen Display Language Japanese/Korean/Norwegian/Polish/Portuguese/Ro manian/Russian/Simplified Chinese/Spanish/Swedish/Thai/Traditional Chinese/Turkish/ Vietnamese (30 Langua)


- Is a trademark of Apple Inc.
- The contrast is measure by full-on/full-off standard.
  Light Source life results will vary depending on environmental conditions and usage.
  Actual product's features and specifications are subject to change without notice.



## INPUT/OUTPUT TERMINALS

## CEILING / WALL MOUNT CHART





# DIMENSIONS





**Benq** 

