# Value-for-money projection performance































ep e en remembre de la companya de l			
Model Name	X1160P	X1160PZ	X1260P
<b>Projection System</b>	DLP®	DLP®	DLP®
Display Panel	0.55" DarkChip™ 1 DMD	0.55" DarkChip™ 1 DMD	0.55" DarkChip™ 2 DMD
Resolution	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)	Native SVGA (800 x 600) Maximum SXGA (1,280 x 1,024), WXGA+ (1,440 x 900)	Native XGA (1,024 x 768) Maximum SXGA+ (1,400 x 1,050),, WXGA+ (1,440 x 900)
Aspect Ratio	4:3 (native), 16:9	4:3 (native), 16:9	4:3 (native), 16:9
Contrast Ratio	2500:1	2700:1	2700:1
Brightness	2,400 ANSI Lumens	2,400 ANSI Lumens	2,400 ANSI Lumens
Lamp Life	4,000 hours	4,000 hours	4,000 hours
Projection Lens	F = 2.41, f = 21.79 mm Manual focus	F = 2.41 ~ 2.55, f = 21.79 mm~23.99 mm 1:1.1 manual zoom and manual focus	F = 2.41 ~ 2.55, f = 21.79 mm~23.99 mm 1:1.1 manual zoom and manual focus
Keystone Correction	±40 degrees (vertical ), manual	±40 degrees (vertical ), manual	±40 degrees (vertical ), manual
Audio	N/A	N/A	One internal speaker with 2 W output
Noise Level	28 dBA	28 dBA	28 dBA
Input Interface	Analog RGB / component video (D-Sub) Composite video (RCA) S-video (mini DIN)	Analog RGB / component video (D-Sub) Composite video (RCA) S-video (mini DIN)	Analog RGB / component video (D-Sub) Composite video (RCA) S-video (mini DIN) PC audio (stereo mini jack)













