Key **Features**

- Designed for Xbox for the ultimate gaming experience
- Immersive audiovisual enjoyment with 4K HDR and Harman-tuned speaker
- Up-to-300" screen size
 with 4,000 ANSI Lumens
 to maximise fun at home
- 4.2ms Ultra-Fast Input &240Hz high refresh rate
- Direct big-screen
 streaming via USB-C



Product **Description**

The PX749-4K is a 4,000 ANSI Lumens 4K home projector designed for Xbox, driving the ultimate gaming experience with Xbox-exclusive resolution and refresh rate combinations. The projector shines in value and brightness as well as delivers pixel-perfect visuals in true 4K UHD clarity with HDR/HLG support. Boasting a Harman-tuned speaker, the PX749-4K elevates audiovisual enjoyment, so you can fully lose yourself in the game. Experience a whole new level of playing with 4.2ms Ultra-Fast Input, a 240Hz refresh rate, and USB-C connectivity for direct streaming from Nintendo® Switch. Set up faster and easier than ever with 1.3x optical zoom, warping, H/V keystone and auto V keystone, capable of creating a screen of up to 300" on any surface. PX749-4K is also a perfect addition to your smart home, with LAN control capability that's compatible with home automation systems and 12V trigger output.

SPECIFICATION

RJ45 (LAN control):

USB Type A (Services):

OTHERS

Native Resolution: 3840x2160 100-240V+/- 10%, Power Supply Voltage: 50/60Hz Brightness: 4000 (ANSI Lumens) (AC in) Contrast Ratio with SuperEco Normal: 310W 12000:1 Power Consumption: Mode: Standby: <0.5W Display Color: 1.07 Billion Colors Operating Temperature: 0~40°C Light Source Type: 240W UHP Lamp Carton: Brown Light Source Life (hours) with Net Weight: 3.0kg 4000 Normal Mode: Gross Weight: 3.9kg Light Source Life (hours) with 20000 SuperEco Mode: Dimensions (WxDxH) with 312x222x108mm Adjustment Foot: F=1.94-2.12, Lens: f=12-15.6mm Packing Dimensions: 415x168x297mm Projection Offset: 120%+/-6% English, French, Spanish, Thai, Throw Ratio: 1.13-1.47 Korean, German, Italian, Russian, Optical Zoom: 1.3x Swedish, Dutch, Polish, Czech, Digital Zoom: 0.8x-2.0x T-Chinese, OSD Language: S-Chinese, Image Size: 30"-300" Japanese, Turkish, Portuguese, Finnish, 0.75m-9.76m Throw Distance: Indonesian, India, (100"@2.50m) Arabic, Vietnamese, Greek, Total 24 H:+/-40°, V:+/-40° Keystone: languages Audible Noise (Normal): 33dB English, S-Chinese, Audible Noise (Eco): 28dB T-Chinese, Indonesian, Finnish, French, German, Input Lag: 4.2ms Italian, Japanese, Korean, Polish, VGA(640 x 480) to Resolution Support: User Guide Language: 4K(3840 x 2160) Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, 480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p **HDTV** Compatibility: Vietnamese, Total 20 languages Horizontal Frequency: 15K-135KHz STANDARD ACCESSORY Vertical Scan Rate: 23-240Hz Power Cord: 1 **INPUT** USB-C Cable: 1 (1m) (HDMI 2.0, HDCP HDMI: Remote Control: 1.4/2.2)(w/backlit) USB Type C: 1 (5V/2A) QSG: Yes **OUTPUT** Warranty Card: Yes (CN Only) Audio-out (3.5mm): **OPTIONAL ACCESSORY** Speaker: 10W Cube Lamp/Light Source: **RLC-127** USB Type A (Power): 1 (5V/1.5A) Wall/Ceiling Mount: PJ-WMK-007 12V Trigger (3.5mm): Carry Bag: PJ-CASE-008 **CONTROL** RS232 (DB 9-pin male):

(share with USB A

Output)