

## L1+ 4K UHD Ultra Short Throw LED Home Projector





- The most compact, economical, true 4K UHD visual experience UST Projector - 8.3 million onscreen pixels, HDR and HLG compatible
- Built with 4LED Technology Enhanced contrast, brightness, color and up to 30,000 hours long lifespan.
- Designed with the environment in mind Built with 50% PCR recycled materials



• Enhanced gaming mode - Low lag gaming

The stylish L1+ is Optoma's most compact, power saving and eco-friendly 4K Ultra-short throw to date.

Designed for environmental sustainability, the L1 Smart maintains brightness and colour saturation for longer with energy-saving LED technology for up to 30,000 hours of maintenance free projection. It's compact and lightweight chassis also features 50% PCR recycled materials in an effort to reduce Optoma's logistical impact on the environment as well as our overall carbon footprint.

## **Specifications**

Display/image	
Display technology	DLPTM
Resolution	UHD (3840x2160)
Brightness	2,500 lumens
Brightness (HK)	2,500
Contrast ratio	1,800,000:1
Native aspect ratio	16:9
Keystone correction - horizontal	-10~+10°
Keystone correction - vertical	-10~+10°
Displayable colours (millions)	1073.4
Horizontal scan rate	15 ~ 145Khz
Vertical scan rate	24 ~ 240Hz
Screen size	1.52m ~ 3.05m (60" ~ 120") diagonal
Lamp info	
Light source type	LED
LED life	30,000 hours
Optical	
Throw ratio	0.25:1
Projection distance	0.47m - 0.59m
Focal length	2.63mm
Native offset	126%
Connectivity	
Connections	Inputs 3 x HDMI 2.0
	Outputs 1 × Audio 3.5mm, 1 × USB-A power 1.5A, 1 × S/PDIF, 1 × Micro-USB
General	
General Noise level (typical)	25dB
Noise level (typical) Noise level (max)	28dB
NOISE IEVEL (IIIdX)	
3D compatibility	Yes (DLP 3D)
3D compatibility 3D	Yes (DLP 3D) Full 3D
3D compatibility 3D Security	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese
3D compatibility 3D Security OSD / display languages	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese,
3D compatibility 3D Security OSD / display languages 360° operation	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85%
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F-104°F, max altitude 10,000ft, max humidity 85% Card style
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85%
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russlan, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85% Card style 2
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Supply	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F-104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote 1x HAKO Mini ATV Dongle
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Supply Power consumption (min) Power consumption (max)	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F-104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote 1x HAKO Mini ATV Dongle 100V ~ 240V, 50-60Hz
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power consumption (min) Power consumption (max)	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F-104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote 1x HAKO Mini ATV Dongle 100V ~ 240V, 50-60Hz 145W
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power consumption (min) Power consumption (max) Weight and dimensions	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F-104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote 1x HAKO Mini ATV Dongle 100V ~ 240V, 50-60Hz 145W
3D compatibility 3D Security OSD / display languages 360° operation Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (min)	Yes (DLP 3D) Full 3D Security bar, Kensington Lock, Password protected interface 11 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) Yes 0-40°C/32°F~104°F, max altitude 10,000ft, max humidity 85% Card style 2 10W 1x Remote 1x HAKO Mini ATV Dongle 100V ~ 240V, 50-60Hz 145W 165W



