

OMA-S Ultra portable RGB triple laser short throw projector





- Cutting-edge RGB triple laser technology and Full HD - Energy saving, vibrant colour and incredible detail
- An impressive short throw lens Bigger screen with same distance and to place the projector closer to the wall
- Ultra portable, compact and flexible design with carry bag Use anywhere, simply point and play
- Auto keystone and focus Automatically adjusts for a clear, sharp and perfectly straight image



The OMA-S is Optoma's most portable, power saving and eco-friendly projectors to date. Weighing just 1kg, its sleek and compact form factor delivers sharp colour, incredible brightness and flexible set-up features for use at home, various immersive installations and on-thego professional environments.

Built with premium RGB triple laser light source technology and Full HD 1080p resolution, the OMA-S features 1,500 HK lumens of brightness and produces accurate, cinema-grade colours for an unrivalled image performance compared with similarly sized projectors. An impressive short throw lens delivers an up to 100-inch image from just over 1.73 metres away from display surfaces.

Specifications

| <u> </u> | |
|---|--|
| Display/image | |
| Display technology | DLPTM |
| Resolution | 1080p Full HD (1920x1080) |
| Brightness (HK) | 1,500 |
| Contrast ratio - dynamic | 3,000,000:1 |
| Native aspect ratio | 16:9 |
| Aspect ratio - compatible | 4:3,16:9 |
| Keystone correction - vertical | +/-40° |
| Has vertical auto keystone | Yes |
| correction | |
| Horizontal scan rate | 15 ~ 140Khz |
| Vertical scan rate | 24 ~ 240Hz |
| Uniformity | 95% |
| Screen size | 0.76m ~ 5.08m (30" ~ 200") diagonal |
| Lamp info | |
| Light source type | Laser |
| LASER life | 30,000 hours |
| Optical | |
| Throw ratio | 0.78:1 |
| Zoom type | Fixed |
| Focal length | 4.049mm |
| Native offset | 100% |
| Connectivity | |
| Connections | Inputs 1 x USB-C power, 1 x HDMI 2.1, 1 x USB-A power |
| | 1.5A, 1 x USB-A power 0.5A, 1 x USB-C |
| | Outputs 1 x Audio 3.5mm |
| | Control 1 x RS232 (via mini USB connector) |
| General | |
| Noise level (typical) | 24dB |
| Noise level (max) | 28dB |
| 3D compatibility | No |
| Security | |
| - | |
| OSD / display languages | Kensington Lock |
| OSD / display languages | |
| | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese |
| Operating conditions | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) |
| Operating conditions Remote control | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft |
| Operating conditions Remote control Speaker count | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes |
| Operating conditions Remote control Speaker count Watts per speaker | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 |
| Operating conditions Remote control Speaker count Watts per speaker | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W |
| Operating conditions Remote control Speaker count Watts per speaker | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote |
| Operating conditions Remote control Speaker count Watts per speaker In the box | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle |
| Operating conditions Remote control Speaker count Watts per speaker In the box Power | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter |
| Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle |
| Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (min) | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle Universal AC 100240V± 10%~ 50 / 60 Hz |
| Operating conditions Remote control Speaker count Watts per speaker In the box Power Power Power supply Power consumption (min) Power consumption (max) | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle Universal AC 100240V± 10%~ 50 / 60 Hz 32W |
| Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (min) Power consumption (max) Weight and dimensions | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle Universal AC 100240V± 10%~ 50 / 60 Hz 32W |
| OSD / display languages Operating conditions Remote control Speaker count Watts per speaker In the box Power Power supply Power consumption (min) Power consumption (max) Weight and dimensions Dimensions (W x D x H) Gross weight | Kensington Lock 10 languages: English, French, German, Italian, Japanese, Portuguese, Russian, Chinese (simplified), Spanish, Chinese (traditional) 0°C ~ 40°C, Max. Humidity 85%, Max. Altitude 2500ft Yes 1 3W Remote Adapter WiFi Dongle Universal AC 100240V± 10%~ 50 / 60 Hz 32W 65.5W |



