

INFOCUS® LP®600 MEETING ROOM PROJECTOR




SEE THE BIGGER PICTURE

With the LP®600, InFocus has brought freedom to your fingertips, combining unrivaled power, access, and simplicity together to give you the world's easiest to use digital projector with PC-free playback. This truly stand-alone projector offers you an impressive selection of connection options — wired or wireless, computer or video sources, and even the option to go PC-free with your USB flash drive — setting you free to focus on a flawless delivery, and not your equipment.

EASE, INCORPORATED

Imagine. Meetings, unencumbered. InFocus ProjectAbility™ is our dedication to making your projection effortless... and powerful. With InFocus LitePort™ technology, the power is at your fingertips, literally. Got a flash drive? You've got a presentation. We make it simple, you make it amazing.



InFocus®

PURE & SIMPLE PERFORMANCE

— EFFORTLESS INTERACTION

The LP600 can set you free, free from lugging PCs and laptops to your meetings, free from wires, and free from hassle. This projector sets a new standard for ease of use, allowing you to simply plug your USB flash drive into the LitePort™ slot, and the projector takes care of the rest, with all the software you'll need built right in. It's ready when you are.

— EFFORTLESS OPTIONS

In addition to the PC-free convenience of LitePort™, the LP600 has the InFocus options that have become industry benchmarks, including wireless interaction through the optional InFocus LiteShow® wireless module, networked control through optional InFocus ProjectorNet™ software and module, intuitive controls and remote, automatic projector orientation, and color-coded inputs for your convenience. Watch downtime and support costs disappear!

— EFFORTLESS BRILLIANCE

Designed in direct consultation with customers like you, the LP600 incorporates true power housed in a stylish, lightweight package. Packed with the latest generation of DLP™ technology from Texas Instruments®, this projector runs quiet and cool while delivering intense radiance and stunning contrast. All at a price that will make your finance manager smile.

FLEXIBILITY. PORTABILITY. COMPATIBILITY. CAPABILITY.

With superior style, simplicity, and power, the LP600 combines the features you need from a meeting room projector with the intuitive interaction experience you have come to expect from InFocus.



Designed in direct consultation with customers like you.



Guarantee the best presentation for your audience.



Flawless delivery that sets you free.



Truly PC-free playback with InFocus LitePort™.

— THE POWER TO PERFORM

With the LP600 at your side, you have the confidence of knowing your presentations will come through as vividly as you envisioned them. InFocus has worked with power users and IT professionals to ensure that this projector meets their exact performance demands, while remaining accessible and flexible for even the casual user. The LP600 offers a bright 2000 lumens (standard mode; 1500 lumens in whisper mode), a contrast ratio of 1000:1, native XGA resolution, and a multitude of connection options, including M1-DA and VESA (the latter selectable as input or loop) for computers, 3.5mm stereo audio input and loop, S-Video and component (RCA) video.

Light weight, slim profile, and quiet operation ensure that this projector will be practically invisible in your meetings. Combined with an intuitive remote, user-defined controls, an LCD display for instant status updates, auto keystone correction, and rich sound capabilities guarantee the best presentation possible for your audience.

— PROJECTABILITY™: IT'S ALL ABOUT EASY

ProjectAbility™ means bringing you the smoothest interaction possible. And that's the design philosophy behind all InFocus products. Never before have you had more options for out-of-the-box control of your projectors, including unparalleled networking, access, and interaction options.

The LP600 expands the ProjectAbility features with the addition of LitePort™, giving LP600 users truly PC-free playback. All you bring with you to the presentation are the files on any standard USB-compatible flash drive, and the projector does the rest. No software, no cables, no hassle. LitePort sets you free to succeed, making this digital presentation device the projector of choice for all your meeting room needs.

If you prefer presenting from your laptop throughout your meetings, you can still demand the ultimate in freedom and flexibility. The InFocus LiteShow® wireless module gives users the ability to communicate wirelessly with the projector over industry-standard Wi-Fi (802.11b) protocols, allowing for easy collaboration. All with intuitive controls, so the LP600 will be ready to shine in a matter of minutes.

For the control of multiple projectors, including the LP600, InFocus ProjectorNet™ allows for remote central management from a single PC over a network. By leveraging the network to remotely troubleshoot and correct user problems, companies, government and universities can reduce support costs and improve productivity.

BRILLIANCE, AT THE SPEED OF LIGHT



- 1 – Computer (M1-DA)
- 2 – Computer In/Monitor Out
- 3 – LitePort™
- 4 – S-Video
- 5 – Composite Video
- 6 – RS-232
- 7 – Audio In
- 8 – Audio Out

PROJECTION DISTANCES/IMAGE SIZES*

Distance to Screen		Min. Diag. Image Size		Max. Diag. Image Size		Min. Horiz. Image Size		Max. Horiz. Image Size	
		Diag/Throw 0.55		Diag/Throw 0.68		Diag/Throw 2.27		Diag/Throw 1.83	
5'	1.5 m	2.75'	0.83 m	3.40'	1.02 m	2.20'	0.66 m	2.73'	0.82 m
10'	3 m	5.50'	1.65 m	6.80'	2.04 m	4.41'	1.32 m	5.46'	1.64 m
15'	4.6 m	8.25'	2.53 m	10.20'	3.13 m	6.61'	2.03 m	8.20'	2.51 m
20'	6.1 m	11.00'	3.36 m	13.60'	4.15 m	8.81'	2.69 m	10.93'	3.33 m
30'	9.1 m	16.50'	5.01 m	20.40'	6.19 m	13.22'	4.01 m	16.39'	4.97 m
32.8'	10 m	18.04'	5.50 m	22.30'	6.80 m	14.45'	4.41 m	17.92'	5.46 m

*Diagonal throw ratio = (distance/diagonal image size); Horizontal throw ratio = (distance/horizontal image size)

THE INFOCUS COMMITMENT

InFocus Corporation's dedication to quality and customer satisfaction is reflected in service options that will bring you a greater return on your investment. InFocus projectors come with a standard limited factory warranty, including parts and labor, and a 90-day lamp replacement warranty. Our customer support offers you premium service and convenience, whatever your needs.

For service program details in your region, please visit www.infocus.com/service/service_offerings

OPTIONAL ACCESSORIES

LP-LITESHOW	Liteshow® wireless connectivity Module
SW-PN2-5CD	ProjectorNet™ asset management software, 5 seat license
HW-CONDUCTOR+	InFocus Conductor+™ remote
HW-PRESENTER	InFocus Presenter™ remote
HW-PRESENTER-RF	InFocus Presenter™ RF remote with receiver
CAC-230	Organizer soft carry case
CA-ATA-020	ATA case
SP-LAMP-019	Replacement lamp
A650	Screen, 50"/127 cm portable
HW-DLXSCRN	Screen, 60"/152 cm Insta-theater
HW-WALLSCR84	Screen, 84"/213 cm wall/ceiling mount
SP-CEIL-011	Universal ceiling mount, meeting/ht
SP-DVI-D	Cable, M1-DA digital computer cable with USB
SP-LOCK-B	InFocus projector cable lock
SP-M1-ADPT	M1 to component adapter

Ships Standard With

- Soft carry case
- Wireless Navigator™ remote control (including batteries)
- Color coded cable straps
- M1-A Computer cable with USB mouse
- Audio cables
- RCA video cable
- Power cord
- Projector System CD includes: multi-language User's Guide, Quick Start Card, URL/service information/accessories
- User's Guide (printed version)
- Quick Start Card (printed version)

TECHNICAL SPECIFICATIONS*

GENERAL

Native Resolution	• XGA 1024 x 768
Display Technology	• DLP™ by Texas Instruments®: 0.7" DDR DDP2000
Computer Compatibility	• SXGA, XGA, SVGA, VGA, Macintosh™, HDTV 1080i, 1080p, 720p, 480p
Video Compatibility	• SDTV (NTSC, PAL, SECAM), ED/HDTV (Component, RGBHV, and DVI for these signal formats: 480p, 576p, 720p, 1080i)
Contrast Ratio	• 1000:1 full on/full off
Projection Lens	• Zoom lens with manual focus and manual zoom adjust
Zoom Ratio	• 1.2:1
Throw Ratio	• 1.83:1 - 2.27:1 (Throw Distance/Image Width)
Projection Distance	• 5' - 32.8' (1.5m - 10.0m)
Image Offset ratio (%)	• 115%
Aspect Ratio	• 4:3 Native Aspect Ratio
Image size (diagonal)	• 26"/66.0 cm to greater than 215"/546.1 cm
Automatic Ceiling Detection	• Yes
Projection Methods	• Front, rear and ceiling

SIZE

Dimensions	• 2.9" (H) x 10.4" (L) x 8.6" (W)/(7.5 cm (H) x 26.3 cm (L) x 21.8 cm (W))
Weight	• 5.2 lbs / 2.4 kg

INPUT

Computer Input Sources	• Computer 1 (M1-A), Computer 2 (VESA), Audio (3.5mm Stereo)
Video Input Sources	• Video 1 (S-Video), Video 2 (Composite RCA)
Control Input Sources	• RS232, USB
Networking	• Yes with optional ProjectorNet™ software and module
Video Input Sources	• Video 1 (S-Video), Video 2 (Composite RCA)
Control Input Sources	• RS232, USB
Computer Free Playback	• LitePort™ PC Free Playback* with USB-compatible flash device
Wireless Connectivity	• Yes with optional LiteShow™ module
Automatic Vertical Keystone Correction	• Yes
Digital Keystone Correction (Vertical)	• +/- 10 degrees: data/video
Projector Control	• Menu, Keypad, ProjectorManager™, RS-232
Mouse Control	• USB

OUTPUT

Output Sources	• Variable Audio (3.5mm Stereo), Monitor Out (VESA)
Audio	• 3.0-Watt
Brightness	• 2000 max ANSI lumens (standard mode) • 1500 max ANSI lumens (whisper mode)
Brightness Uniformity	• -30% (ANSI) Typical
Number of Colors	• 16.7 million
Projector Interface	• Interactive LCD Display or Menu system
Projector Interface Languages	• English, Spanish, French, German, Japanese, Korean, Portuguese, Italian, Norwegian, Russian, Chinese Simple, Chinese Traditional
Lamp	• 200W SHP / 2000 hours*

OTHER

H-Synch Range	• 31 - 85 kHz
V-Synch Range	• 50 - 85 Hz
Dot Clock	• 140 MHz
Power Consumption	• 260 watts
Power Supply	• 85V - 240V at 50/60 Hz
Operating Temperature	• 10° - 40°C at sea level (0 to 10,000'); 50° - 104° F
Audible Noise	• 35dB (whisper mode) • 37dB (standard mode)
Approvals	• FCC A (US/Canada), UL & cUL (US/Canada), GOST (Russia), TUV GS (Germany), CCC (China), IRAM (Argentina), NOM (Mexico), MIC (Korea), C-Tick (Australia)
Lamp Warranty	• 90 days exchange (or 500 hours, whichever come first)

*Actual lamp life may vary based on the ambient environment. Conditions that may affect lamp life include temperature, altitude or rapidly switching the projector on and off.

+InFocus reserves the right to alter product offerings and specifications at any time without notice.

Contact InFocus or your dealer today.

www.infocus.com

InFocus Corporate Headquarters:
27700B SW Parkway Avenue • Wilsonville, Oregon 97070-9215, USA
Phone: 503-685-8888 • 1-800-294-6400 • Fax: 503-685-8887

In Europe: InFocus International BV
Strawinskylaan 585 • 1077 XX Amsterdam • The Netherlands
Phone: (31) 20 5792000 • Fax: (31) 20 5792999
Freephone: 008000 4636287 (008000 INFOCUS)

In Asia: InFocus Systems Asia Pte Ltd.
238A Thomson Road • #18-01/04 Novena Square
Singapore 307684 • Phone: (65) 6334-9005 • Fax: (65) 6333-4525

InFocus, LiteShow, LitePort, ProjectAbility, ProjectorNet, ProjectorManager and LP are trademarks or registered trademarks of InFocus Corporation or its subsidiaries in the United States and other countries. Digital Light Processing and DLP are trademarks of Texas Instruments. All other trademarks are used with permission or are for identification purposes only and are the property of their respective companies. ©2004 InFocus Corporation. All rights reserved. 805-0980.00 LP600_DS_E_V00.qxd 6/04