

PowerLite® L690SE / L695SE

6,000-Lumen Short Throw 3LCD
Laser Projector with 4K Enhancement



This incredibly compact projector delivers larger-than-life images with a short 0.5 – 0.7 throw ratio.



Bright, true-to-life images — 3-chip 3LCD technology and 6,000 lumens of equal color and white brightness²

WUXGA with 4K Enhancement Technology¹ — accepts 4K content and displays double HD resolution on-screen; enjoy a visibly sharper, more detailed picture even at close viewing distances

Short throw lens with powerful optical zoom — with a 0.5 – 0.7 throw ratio and 1.4x optical zoom, achieve large images from a close distance; perfect for projecting onto a floor or from behind a screen

Large, versatile display options — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

Simplified installation — compact and lightweight design featuring a wide vertical and horizontal lens shift, 1.4x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

Low maintenance — up to 30,000-hour laser light source and air filter³ in Extended Mode

Built-in NFC⁴ — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool app

Optional attachable PixAlign™ camera — adds powerful multi-projector tools including screen matching⁵, auto color calibration⁵, blending assist⁶ for super wide displays and simple stacking⁶ without an external PC

Over-the-air updates⁷ — allows user to optionally be alerted when a Firmware update is available

Enhanced connectivity — HDBaseT® and HDMI® two in and one out for daisy-chaining and signal monitoring

Specifications

Projection System RGB liquid crystal shutter projection system
Projection Method Front/rear/ceiling mount
LCD Size 0.67" (C/Fine)
Driving Method Poly-Silicon TFT Active Matrix
Pixel Number 2,304,000 dots (1920 x 1200) x 3
Native Resolution WUXGA with 4K Enhancement¹ (1920 x 1200 x 2)
Resolution On-Screen WUXGA with 4K Enhancement¹/ 4.6 million pixels
Resize 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050
Aspect Ratio Supports 4:3, 16:10, 16:9*, 16:6*, 21:9*
 * With vertical image shift control within letterbox area.
Pixel Arrangement Cross stripe
Color Brightness² Color light output: 6,000 lumens
White Brightness² White light output: 6,000 lumens
Contrast Ratio Up to 5,000,000:1
Brightness Uniformity (Typical) 88%
Color Reproduction Up to 1.07 billion colors
Size (Projected Distance) 100" – 500"
Projected Distance 80" screen 1.38 m
Lens Shift Vertical: ±50%; Horizontal: ±20%
Keystone Correction Vertical: ±30 degrees; Horizontal: ±30 degrees
Light Source Laser Diode
Light Source Life³ Normal: 20,000 hours; Quiet: 20,000 hours; Extended: 30,000 hours

Projection Lens (Short Throw)

Type Optical Zoom (manual)/Focus (manual)/Corner focus (manual)
F-Number 1.8 – 2.0
Focal Length 7.54 mm – 10.55 mm
Zoom Ratio 1.0 – 1.4x (optical)
Throw Rate Range 0.5 – 0.7 (optical)
Lens Cover Lens cap (without string)

Other Features

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C)
Power Supply Voltage 100 V – 240 V ± 10%, 50/60 Hz AC
Auto Power On Signal Detection on HDMI/Plug-In Detection (HDMI, USB, VGA 15-Pin, BNC)
Sleep Mode Yes (with timer)
HDMI CEC Control Yes
Power Consumption
 432 W (Normal Mode)
 313 W (Quiet and Extended)
 2.4 W (Standby comm on)
 0.3 W (Standby comm off)
Fan Noise 36 dB (Normal Mode); max. 26 dB (ECO Mode)
Security Security cable hole, Kensington® lock provision
A/V Mute Yes
Speaker(s) N/A
Split Screen⁴ Yes (up to 2 screens)
Content Playback Yes
Quick Corner Yes
Arc Correction Yes
Edge Blending Yes

Interfaces

HDMI (HDCP 2.3) x 2
 HDMI Out x 1
 HDBaseT x 1
 Variable Audio Out: Mini Stereo x 1
 USB Connector Type-A x 1
 USB Connector Type-B x 1
 Serial: RS-232c x 1
 Wired LAN RJ45 x 1

Other Features (Continued)

Screen Sharing Yes
Corner Wall Yes
Curved Surface Yes
Camera Yes

Effective Scanning Frequency Range (Digital)

Pixel Clock 25.1 MHz to 594 MHz
Horizontal 26 kHz to 135 kHz
Vertical 23.98/24/25/29.97/30/50/59.94/60 Hz

Dimensions (W x D x H)

Excluding Feet 17.32" x 11.97" x 4.80"
Including Feet 17.32" x 14.25" x 5.94"
Weight 20.5 lb

Network and Remote Control

Features Power, source search selection, A/V Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions
Operating Angle Rear: Right/Left: -55 to +55 degrees; Upper/Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees
Operating Distance 26 ft (8 m)
Network Control PLink, Crestron Integrated partner, Crestron Connected V2 with Xio Cloud, Extron IP link, Extron XTP, AMX, Control4

Eco Features

RoHS compliant
 End-of-life options available⁹
 Epson America, Inc. is a SmartWay® Transport Partner¹⁰
 Design and Manufacturing centers utilize 100% renewable electricity
 Dynamic Contrast (ECO) Mode reduces power consumption by 36%



L695SE Black



L690SE White

Limited Warranty and Service

Warranty Three-year limited in the U.S. and Canada
Service Whole unit exchange, usually Next-Business-Day
 Toll-free telephone support, Monday through Friday
Epson Connection™
 Pre-Sales Support (United States and Canada): 800-463-7766
 Website: www.epson.com

Epson Preferred Plus™ Extended Service Plan¹¹

1-Year Next-Business-Day Whole Unit Exchange¹² EPPEXPE1
 2-Year Next-Business-Day Whole Unit Exchange¹² EPPEXPE2
 (available for up to a total of 5 years of continuous coverage)

What's Included

PowerLite L690SE / L695SE projector, power cable, projector remote control with batteries, Quick Setup sheet, cable cover and Quick Setup poster

Ordering Information & Accessories

PowerLite L690SE (White)	V11HB36020
PowerLite L695SE (Black)	V11HB36120
Replacement Air Filter (ELPAF65)	V13H134AF0
Universal Projector Mount (ELPMBPJG)	V12H808001
Custom Micro-Adjustable Projector Mount (ELPMBPRH)	V12H809001
Wireless LAN module (ELPAP11)	V12H005A02
PowerLite Pilot™ 3R (ELPCB03N)	V12HB11020
PixiePlus	ELPSP10
External Speaker (ELPSP02)	V12H467020
DC-07 Document Camera	V12H759020
DC-13 Document Camera	V12H757020
DC-21 Document Camera	V12H758020
PixAlign Camera (ELPEC01)	V12HA46010

1 4K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. | 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. | 3 No required maintenance for the light source and filter for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. | 4 NFC requires use of a device that includes NFC and may require additional software. | 5 Using separate camera for each projector. | 6 Requires Epson external camera or built-in camera for each projector and the Epson Projector Professional Tool app. | 7 Requires an active Internet connection for alerts and Firmware download. | 8 Split Screen feature requires remote control. Consult your user manual for input combinations. | 9 For convenient and reasonable recycling options, visit epson.com/recycle | 10 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65489 3/25

See the latest innovations from Epson Business Solutions at epson.com/forbusiness



Epson America, Inc.
 3131 Katella Ave., Los Alamitos, CA 90720

Epson Canada Limited
 185 Renfrew Drive, Markham, Ontario L3R 6G3

www.epson.com
www.epson.ca

Specifications and terms are subject to change without notice. EPSON, the 3LCD logo and PowerLite are registered trademarks and Epson iProjection is a trademark of Seiko Epson Corporation. Epson Connection, Epson Preferred Plus, Pilot and PixAlign are trademarks of Epson America, Inc. SmartWay is a registered trademark of the U.S. Environmental Protection Agency. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. Copyright 2025 Epson America, Inc. CPD-65489 3/25

Contact:

