

## PowerLite® L890U

8,000-Lumen WUXGA 3LCD Laser Projector



Experience an ultra bright and compact projector with pro-level features.







**Ultra bright, true-to-life images** — 3-chip 3LCD technology and 8,000 lumens of equal color and white brightness<sup>2</sup>

**Full HD WUXGA resolution** — accepts up to 4K signal and provides 1920 x 1200 resolution for vibrant, high-definition images

**Large, versatile display options** — easily create a display up to 500" diagonal in 16:10, plus ultra wide 16:6 and 21:9 aspect ratios for enhanced content display and visibility

**Simplified installation** — compact and lightweight design featuring wide vertical and horizontal lens shift, 1.6x optical zoom, 360-degree mounting, built-in geometric correction tools and a universal VESA mounting pattern

**Low maintenance** — up to 30,000-hour laser light source and air filter<sup>3</sup> in Extended Mode

**Wireless networking and content sharing**<sup>4</sup> — Wi-Fi<sup>®</sup> 6/6E allows for fast, reliable wireless connectivity for screen casting<sup>4</sup>, along with direct connection to the cloud-based service, Epson Projector Management Connected and WPA3-Enterprise security

**Built-in NFC**<sup>5</sup> — reduces installation time of multiple projectors; read and write setting information using the Epson Projector Config Tool app

**Optional attachable PixAlign™ camera** — adds powerful multiprojector tools including screen matching<sup>6</sup>, auto color calibration<sup>6</sup>, blending assist<sup>7</sup> for super wide displays and simple stacking<sup>7</sup> without an external PC

**Over-the-air updates**<sup>8</sup> — allows user to optionally be alerted when a Firmware update is available

 $\label{eq:connectivity} \textbf{Enhanced connectivity} - \textbf{HDBaseT}^{\texttt{@}} \ \text{and HDMI}^{\texttt{@}} \ \text{two in and one} \\ \text{out for daisy-chaining and signal monitoring}$ 

# **EPSON**<sup>®</sup>

## PowerLite® L890U 8,000-Lumen WUXGA 3LCD Laser Projector

#### **Specifications**

Projection System RGB liquid crystal shutter projection system
Projection Method Front/rear/ceiling mount

LCD Size 0.67" (C2Fine)

Driving Method Poly-Silicon TFT Active Matrix
Pixel Number 2,304,000 dots (1920 x 1200) x 3
Native Resolution 1920 x 1200 (WUXGA)
Resolution On-Screen 1920 x 1200 (WUXGA)
Resize 640 x 480, 800 x 600, 1280 x 1024, 1400 x 1050
Aspect Ratio Supports 4:3, 16:10, 16:9\*, 16:6\*, 21:9\*
\* With vertical image shift control within letterbox area.

Pixel Arrangement Cross stripe

**Color Brightness**<sup>2</sup> Color light output: 8,000 lumens **White Brightness**<sup>2</sup> White light output: 8,000 lumens

Contrast Ratio Over 5,000,000:1 Brightness Uniformity (Typical) 88% Color Reproduction Up to 1.07 billion colors Size (Projected Distance) 50" – 500"

**Projected Distance** 80" screen 2.33 m - 3.78 m **Lens Shift (Manual)** Vertical: ±50%; Horizontal: ±20%

 $\textbf{Keystone Correction} \ \mathsf{Vertical: \pm 30 \ degrees};$ 

Horizontal: ±30 degrees **Light Source** Laser Diode

Laser Light Source Life<sup>3</sup> Normal: 20,000 hours; Quiet: 20,000 hours: Extended: 30,000 hours

#### **Projection Lens (Standard)**

Type Optical Zoom (manual)/Focus (manual)

**F-Number** 1.5 – 1.7

Focal Length 20.0 mm – 31.8 mm
Zoom Ratio 1.0 – 1.6x (optical)
Throw Rate Range 1.35 – 2.20 (optical)
Lens Cover Lens cap (without string)

#### **Wireless Specifications**

Frequency Type (Modulations) 802.11 b/g/n/ac/ax (2.4 GHz) Supported Security Type Quick Mode: Open, WPA2/WPA3-PSK, WPA2/WPA3-EAP; Advanced Mode: WPA/WPA2-PSK, WPA/WPA2-EAP

#### **Other Features**

Operating Temperature 32 °F to 113 °F (0 °C to 45 °C) Power Supply Voltage 100 V - 240 V  $\pm$  10%, 50/60 Hz AC Auto Power On Signal Detection on HDMI/Plug-In Detection Sleep Mode Yes (with timer)

HDMI CEC Control Yes

#### Power Consumption

470 W (Normal Mode) 341 W (Quiet and extended) 2.4 W (Standby comm on)

0.3 W (Standby comm off)

Fan Noise 31 dB (Normal Mode); max. 23 dB (ECO Mode) Security Security cable hole, Kensington® lock provision Miracast®4 Yes

Epson iProjection™ Yes (V4)
Split Screen9 Yes (up to 2 screens)

#### Interfaces

HDMI (HDCP 2.3) x 2 HDMI Out x 1 HDBaseT x 1 Variable Audio Out: Mini Stereo x 1 USB Connector Type-A x 1 USB Connector Type-B x 1 Serial: RS-232c x 1 Wired LAN RJ45 x 1 Wireless LAN: Built-in



#### **Other Features (Continued)**

A/V Mute Yes Camera Yes

Speaker(s) 10 W (mono)
Content Playback Yes
Quick Corner Yes
Corner Wall Yes
Curved Surface Yes
Edge Blending Yes

Screen Sharing Yes

## **Effective Scanning Frequency Range (Digital)**

Pixel Clock 25.1 MHz – 594 MHz Horizontal 26 kHz – 135 kHz

Vertical 23.98/24/25/29.97/30/50/59.94/60 Hz

#### **Dimensions (W x D x H)**

Excluding Feet 17.32" x 11.97" x 4.80" Including Feet 17.32" x 13.39" x 5.43" Weight 19.1 lb

#### **Network and Remote Control**

Features Power, source search selection, AV Mute, number input, menu, esc, select, Freeze, ID, Customize, E-Zoom, mute, volume, playback control and pointer functions

Operating Angle Rear: Right/Left: -55 to +55 degrees; Upper/ Lower: +75 to +15 degrees; Front: Right/Left: -30 to +30 degrees; Upper/Lower: 0 to +60 degrees

Operating Distance 26 ft (8 m)

Network Control PJLink, Creston Integrated partner, Crestron
Connected V2 with XiO Cloud. Extron IP link. Extron XTP. AMX. Control4

### **Eco Features**

RoHS compliant

End-of-life options available<sup>10</sup>

Epson America, Inc. is a SmartWay® Transport Partner<sup>11</sup>

Design and Manufacturing centers utilize 100% renewable electricity Dynamic Contrast (ECO) Mode reduces power consumption by 36%

### **Limited Warranty and Service**

Warranty Three-year limited in the U.S. and Canada Service Whole unit exchange, usually Next-Business-Day Toll-free telephone support, Monday through Friday

**Epson Connection**<sup>™</sup>

Pre-Sales Support (U.S. and Canada): 800-463-7766 Website: www.epson.com

#### Epson Preferred Plus™ Extended Service Plan<sup>12</sup>

1-Year Next-Business-Day Whole Unit Exchange<sup>13</sup> EPPEXPE1
2-Year Next-Business-Day Whole Unit Exchange<sup>13</sup> EPPEXPE2
(available for up to a total of 5 years of continuous coverage)

#### What's Included

PowerLite L890U laser projector, power cable, projector remote control with batteries, Quick Reference card, cable cover

#### **Ordering Information & Accessories**

V11HB27020 PowerLite L890U Replacement Air Filter (ELPAF65) V13H134AF0 Custom Micro-Adjustable Projector Mount (ELPMBPRH) V12H809001 Universal Projector Mount (ELPMBPJG) V12H808001 PowerLite Pilot™ 3 (ELPCB03) V12H927020 PixiePlus ELPSP10 PixAlign Camera (ELPEC01) V12HA46010 External Speaker (ELPSP02) V12H467020 DC-07 Document Camera V12H759020 DC-13 Document Camera V12H757020 DC-21 Document Camera V12H758020

14K Enhancement Technology shifts each pixel to surpass Full HD resolution on screen. I 2 Color brightness (color light output) and white brightness (white light output) will vary depending on usage conditions. Color light output measured in accordance with IDMS 15.4; white light output measured in accordance with ISO 21118. I 3 No required maintenance for the light source and filter for up to 30,000 hours (Extended Mode) or 20,000 hours (Normal Mode). Approximate time until brightness decreases 50% from first usage. Measured by acceleration test assuming use of 0.04 - 0.20 mg/m³ of particulate matter. Time varies depending on usage conditions and environment. Replacement of parts other than the light source may be required in a shorter period. I 4 The projector supports direct peer-to-peer wireless casting of local content from Miracast-enabled devices or via the Epson iProjection app. For best performance when using Epson iProjection, it is recommended that the projector and connecting devices be configured on a network, either through the Ethernet port on the projector or via a wireless connection. The Epson iProjection App does not support all files and formats. See epson.com/iprojection for details. I 5 NFC requires use of a device that includes NFC and may require additional software. I 6 Using separate camera for each projector. I 7 Requires Epson external camera for each projector and may require Epson Projector Professional Tool app. I 8 Requires an active Internet connection for alerts and Firmware download. I 9 Split Screen feature requires remote control. Consult your user manual for input combinations. I 10 For convenient and reasonable recycling options, visit epson.com/recycle I 11 SmartWay is an innovative partnership of the U.S. Environmental Protection Agency that reduces greenhouse gases and other air pollutants and improves fuel efficiency. I 12 Product comes with a 3-year limited warranty or Epson Extended Service Plans up to a total of 5 years of continuous coverage. Extended Service Plan

See the latest innovations from Epson Business Solutions at epson.com/forbusiness

