

Key Features

- Innovative home installation projector with RGB laser technology
- Unmatched colour performance with 100% coverage of the BT.2020 colour space
- 5,200 RGB Laser Lumens for uninterrupted big-screen fun in any lighting condition
- True 4K HDR immersive visuals and high contrast enabled by a 0.65-inch DMD chip
- Flexible installation options: 1.6x optical zoom, vertical lens shift, and H/V keystone correction



Product Description

The V57-4K projector sets a new standard in home cinema with its RGB laser technology, enhancing image quality for an exceptional viewing experience. Utilising advanced laser projection, it achieves 100% BT.2020 colour gamut coverage, delivering vivid, lifelike colours that bring your favourite shows to life. With 5,200 RGB Laser Lumens, 4K UHD resolution, and HDR/HLG support, it ensures a bright, crystal-clear, vibrant viewing experience at any time. The projector's high contrast ratio, powered by the Texas Instruments 0.65-inch DMD chip, reveals intricate details in dark scenes and enriches blacks for complete visual immersion. Its 1.6x optical zoom, vertical lens shift, and side projection capabilities, complemented by H/V keystone and 4-corner adjustment, offer versatile installation options, making setup and home cinema upgrades effortless. As one of the first "Designed for Xbox" projectors, it also provides outstanding gaming performance at an optimal 1440p@120Hz, ensuring total immersion in all your home entertainment pursuits.

SPECIFICATION

Projection System:	0.65" 4K-UHD	OTHERS	Power adaptor: Input: 100~240V Output: 19.5VDC / 9.23A
Native Resolution:	3840x2160	Power Supply Voltage:	Normal: 145W Standby: <0.5W
Brightness:	5200 (RGB Laser Lumens)	Power Consumption:	0~40°C
Contrast Ratio:	3000000:1	Operating Temperature:	0~40°C
Display Color:	1.07 Billion Colors	Carton:	Brown
Light Source Type:	RGB Laser	Net Weight:	2.70kg
Light Source Life (hours) with Normal Mode:	20000	Gross Weight:	4.00kg
Light Source Life (hours) with SuperEco Mode:	30000 (Eco)	Dimensions (WxDxH) with Adjustment Foot:	286x216x129mm
Lens:	F=2.5-3.26, f=20.911-32.62mm	Packing Dimensions:	400x280x155mm
Projection Offset:	137%+/-10%	OSD Language:	English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, Arabic, Vietnamese, Greek, Norsk. Total 23 languages
Throw Ratio:	1.4-2.24	User Guide Language:	English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, total 20 languages
Optical Zoom:	1.6x	STANDARD ACCESSORY	
Digital Zoom:	0.8x-2.0x	Power Cord:	1
Image Size:	30"-300"	Remote Control:	1 (w/ backlit)
Throw Distance:	0.93-14.88m (100" @ 3.10m)	QSG:	Yes
Keystone:	H:+/-30° , V:+/-30°	Warranty Card:	Yes (CN Only)
Lens Shift V. Range:	+0%, -15%	OPTIONAL ACCESSORY	
Audible Noise (Normal):	30dB	Wall/Ceiling Mount:	PJ-WMK-007
Audible Noise (Eco):	27dB	Carry Bag:	PJ-CASE-008
Input Lag:	4.2ms		
Resolution Support:	VGA(640 x 480) to 4K(3840 x 2160)		
HDTV Compatibility:	480i, 480p, 576i, 576p, 720p, 1080i, 1080p, 2160p		
Horizontal Frequency:	15K-255KHz		
Vertical Scan Rate:	23-240Hz		
INPUT			
HDMI:	2 (HDMI 2.0/ HDCP 2.2)		
OUTPUT			
Audio-out (3.5mm):	1		
Audio-out (HDMI ARC):	1 (eARC) (Share with HDMI Input)		
Speaker:	15W		
USB Type A (Power):	2 (USB2.0 - 5V/0.5A x1, USB2.0 - 5V/1.5A x1, share with USB A Service)		
12V Trigger (3.5mm):	1		
CONTROL			
RS232 (DB 9-pin male):	1		
USB Type A (Services):	1 (share with USB A Output)		